# Apache

Project: \_\_\_\_\_\_
Type:




Bollard & Pole | topLED 7 W | CRI 80 | 4000K | General Lighting | Sand | Wet location | 180mA

l IP6

LL-E64265-N-00



Technical data		
Designer	Studio RIGO	
Туре	Bollard	
Installation position	Floor	
Installation environment	Outdoor	
Light Source	LED	
Optics	General Lighting	
Light emission direction	downward	
Power	7 W	
Operation	180mA	
Source lumens	1087 lm	
ССТ	4000 K	
Color rendering index	80 Ra	
Safety class	Class 2	
IP	IP65	
IK	IK08	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	Yes	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	No	
Resin potting	No	
Type of light emission	Single emission	
Net weight	1,78 Kg	
Electrostatic discharge protection	4 KV	
Surge protection	0,5 KV	
Ordinary temperature on the glass	104 °F	



Finishing casing	
Material	Aluminum 6060
Color	Sand
Process	Open pore anodizing + Powder Coating

Finishing diffuser	
Material	UV Resistant Polycarbonate
Color	opaline

Finishing base	
Material	Galvanised Iron
Color	Dark brown
Process	Powder coating

Notes:			
			_

## Apache



Bollard & Pole | topLED 7 W | CRI 80 | 4000K | General Lighting | Sand | Wet location | 180mA | Base

## LL-E64265-N-00

Single emission bollard & pole for outdoor application. The natural white LED light source with a general lighting light distribution is composed of 4 powerled LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 1087 lm, with a 155.3 lm/W nominal luminous efficacy.


The device body is made of aluminium 6060 and features a sand finish, processed by means of open pore anodizing + powder coating; the diffuser is made of uv resistant polycarbonate. The ingress protection degree is IP65; the total weight is of 2.205 lbs.

The total absorbed power is 7 W.

and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

# 90° 75° 75° 75° 45° 45° 45° 45° 750 900 30° 15° 0° 15° 30° Cd/kim η = 100%



## Energy efficiency class

This product contains a light source of energy efficiency class D.

Led features	
Light Output Ratio (LOR)	44 %
Source lumens	1087 lm
Delivered lumens	487 lm
Power	7 W
Luminaire efficacy	69 lm/W
Color temperature	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Color rendering index	80 Ra
LED Life / Failure Ratio	
L70 B20 C10 108000h (at Tj 65 Ta 25 )	

OPTICAL		
Light distribution symmetry	Symmetrical 2	
C0/C180 optics	68°	

# Apache



Apache | Bollard & Pole | Accessories LL-E64265-N-00

Anchor - Tie rods

installation position: floor,Cover material: aisi 304 steel

**Code** E64210

3/3 inter-lux inter-lux.com/linealight