Apache

Project: ______
Type:




Bollard & Pole | topLED 7 W | CRI 80 | 4000K | General Lighting | Dark brown | Wet location | 180mA

) IP6

LL-E64264-N-00



Technical data			
Designer	Studio RIGO		
Туре	Bollard		
Installation position	Floor		
Installation environment	Outdoor		
Light Source	LED		
Optics	General Lighting		
Light emission direction	downward		
Power	7 W		
Operation	180mA		
Source lumens	1087 lm		
ССТ	4000 K		
Color rendering index	80 Ra		
Safety class	Class 2		
IP	IP65		
IK	IK08		
Glow wire test	850°		
Direct mounting on normally flammable surfaces	Yes		
CE	Yes		
ETL	Yes		
Dimmable article	No		
Directional	No		
Tilting	No		
Walk-over	No		
Drive-over	No		
Cable included	No		
Resin potting	No		
Type of light emission	Single emission		
Net weight	1,78 Kg		
Electrostatic discharge protection	4 KV		
Surge protection	0,5 KV		
Ordinary temperature on the glass	104 °F		



Finishing casing			
Material	Aluminum 6060		
Color	Dark brown		
Process	Open pore anodizing + Powder Coating		

Finishing diffuser	
Material	UV Resistant Polycarbonate
Color	opaline

Finishing base					
Material	Galvanised Iron				
Color	Dark brown				
Process	Powder coating				

Notes:			

Apache



35 %

1087 lm

385 lm

55 lm/W

4000 K

7 W

Bollard & Pole | topLED 7 W | CRI 80 | 4000K | General Lighting | Dark brown | Wet location | 180mA | Base

LL-E64264-N-00

Single emission bollard & pole for outdoor application. The natural white LED light source with a general lighting light distribution is composed of 4 powerled LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 1087 lm, with a 155.3 lm/W nominal luminous efficacy.

The device body is made of aluminium 6060 and features a dark brown finish, processed by means of open pore anodizing + powder coating; the diffuser is made of uv resistant polycarbonate. The ingress protection degree is IP65; the total weight is of 2.205 lbs.

The total absorbed power is 7 W.

and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Color temperature Standard Deviation of Colour Matching 3 Step MacAdam Color rendering index 80 Ra LED Life / Failure Ratio L70 B20 C10 108000h (at Tj 65 Ta 25) OPTICAL Light distribution symmetry Symmetrical 2 C0/C180 optics 68°

This product contains a light source of energy efficiency class D.

Energy efficiency class

Light Output Ratio (LOR)


Led features


Source lumens

Power

Delivered lumens

Luminaire efficacy





Apache



Apache | Bollard & Pole | Accessories LL-E64264-N-00

Anchor - Tie rods

installation position: floor, Cover material: aisi 304 steel

Code

E64210