Apache	

Bollard & Pole topLED 7 W CRI 80 3000K General Lighting Anthracite R/	AL 7021
Wet location 180mA	
LL-E64262-W-00	

Project:

Type:

Technical data	
Designer	Studio RIGO
Туре	Bollard
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	7 W
Operation	180mA
Source lumens	1034 lm
ССТ	3000 K
Color rendering index	80 Ra
Safety class	Class 2
IP	IP65
IK	IK08
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	Yes
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	1,78 Kg
Electrostatic discharge protection	4 KV
Surge protection	0,5 KV
Ordinary temperature on the glass	104 °F

$\begin{array}{c|c} & & & \\ & &$

1.9

2.4

Material	Aluminum 6060 Anthracite RAL 7021	
Color		
Process	Open pore anodizing + Powder Coating	
Finishing diffu	Iser	
Material	UV Resistant Polycarbonate	
Color	opaline	
Finishing base	e	
Material	Galvanised Iron	
Color	Anthracite RAL 7021	
Process	Powder coating	

Notes:

15.09.2022

0



Apache

Bollard & Pole | topLED 7 W | CRI 80 | 3000K | General Lighting | Anthracite RAL 7021 | Wet location | 180mA | Base LL-E64262-W-00

Single emission bollard & pole for outdoor application. The warm white LED light source with a general lighting light distribution is composed of 4 powerled LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 1034 lm, with a 147.7 lm/W nominal luminous efficacy.

The device body is made of aluminium 6060 and features a grey ral 7021 finish, processed by means of open pore anodizing + powder coating; the diffuser is made of uv resistant polycarbonate. The ingress protection degree is IP65; the total weight is of 2.205 lbs.

The total absorbed power is 7 W.

and can be floor-mounted.


Compliant with the EN 60598-1 standard and its specific provisions.


Energy efficiency class

This product contains a light source of energy efficiency class D.

Light Output Ratio (LOR)	35 %
Source lumens	1034 lm
Delivered lumens	366 lm
Power	7 W
Luminaire efficacy	52 lm/W
Color temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Color rendering index	80 Ra
LED Life / Failure Ratio	
L70 B20 C10 108000h (at Tj 65 Ta 25)	

OPTICAL	
Light distribution symmetry	Symmetrical 2
C0/C180 optics	68°





40

22

0 14

Apache

Apache | Bollard & Pole | Accessories LL-E64262-W-00

Anchor - Tie rods installation position: floor,Cover material: aisi 304 steel **Code** E64210