Bibok

Project: ______
Type:




Downlights | 1 x 5mmLED 0.5 W | CRI 75 | 3500K | Flood | Embossed white RAL 9003 | Damp location | 24V



LL-E91366-T-30







Technical data	
Туре	Encasement without flange
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Light Source	LED
Optics	Flood
Light emission direction	downward
Power	0.5 W
Operation	24V
Voltage	24V
CCT	3500 K
Color rendering index	75 Ra
Safety class	Class 2
IP	IP44
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	Yes
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	0.39 ft
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.02 lbs
Electrostatic discharge protection	No
Surge protection	No

104 °F

Material	OT58 brass	
Color	Embossed white RAL 9003	
Process	Powder coating	

Cables Electrification			
Cable connector	No		

Notes:			

Ordinary temperature on the glass

Bibok



Downlights | 1 x 5mmLED 0.5 W | CRI 75 | 3500K | Flood | Embossed white RAL 9003 | Damp location | 24V **LL-E91366-T-30**

Single emission downlights for indoor application. The 3500 LED light source with a flood light distribution is composed of 1 5mmled LEDs with CCT of 3500 K and a CRI 75.

The device body is made of ot58 brass and features a embossed white ral 9003 finish, processed by means of powder coating. The ingress protection degree is IP44; the total weight is of 0.022 lbs.

The total absorbed power is 0.5 W. The power supply cable is included and features a 0.394 ft lenght.

and can be wall lights or ceiling-mounted, with a 0.276 in diameter hole (in plasterboard).

Compliant with the EN 60598-1 standard and its specific provisions.

Led features		
Color temperature	3500 K	
Color rendering index	75 Ra	