Bibok

Project: Type:




Downlights | 1 x 5mmLED 0.5 W | CRI 75 | 3500K | Flood | Chrome | Damp location | 24V LL-E85335-T-30









0.3

Finishing casing				
Material	OT58 brass			
Color	chrome			
Process	Galvanic Chromium Plating			
Cables Electri	fication			

Notes:			

Cable connector

Technical data				
Туре	Encasement without flange			
Installation position	Wall lights - Ceiling			
Installation environment	Indoor			
Light Source	LED			
Optics	Flood			
Light emission direction	downward			
Power	0.5 W			
Operation	24V			
Voltage	24V			
ССТ	3500 K			
Color rendering index	75 Ra			
Safety class	Class 2			
IP	IP44			
Glow wire test	850°			
Direct mounting on normally flammable surfaces	Yes			
CE	Yes			
ETL	Yes			
Dimmable article	No			
Directional	No			
Tilting	No			
Walk-over	No			
Drive-over	No			
Cable included	Yes			
Cable length	0.39 ft			
Resin potting	Yes			
Type of light emission	Single emission			
Net weight	0.02 lbs			
Electrostatic discharge protection	No			
Surge protection	No			
Ordinary temperature on the glass	104 °F			

Bibok



Downlights | 1 x 5mmLED 0.5 W | CRI 75 | 3500K | Flood | Chrome | Damp location | 24V **LL-E85335-T-30**

Single emission downlights for indoor application. The 3500 LED light source with a flood light distribution is composed of 1 5mmled LEDs with CCT of 3500 K and a CRI 75.

The device body is made of ot58 brass and features a chrome finish, processed by means of galvanic chromium plating. The ingress protection degree is IP44; the total weight is of 0.022 lbs.

The total absorbed power is 0.5 W. The power supply cable is included and features a 0.394 ft lenght.

and can be wall lights or ceiling-mounted, with a 0.276 in diameter hole (in plasterboard).

Compliant with the EN 60598-1 standard and its specific provisions.

Led features				
Color temperature	3500 K			
Color rendering index	75 Ra			