Bond_Pro

Project: Type:



Bollard & Pole | 120-277 V | topLED 10.8 W | CRI 80 | 4000K | General Lighting | Gray RAL 9006 | Wet location | 120V/277V



+ 0-10V interface

LL-E81101-N-00



Ø7.7		
20.1		2.3
	<u> </u>	

Technical data	
Туре	Gray RAL 9006
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	10.8 W
Operation	120V/277V + 0-10V interface
Source lumens	1460 lm
Frequency	50 - 60 Hz
ССТ	4000 K
Color rendering index	80 Ra
Safety class	Class 2
IP	IP65
IK	IK07
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	Yes
Driver included	Integral driver
Dimmable article	0-10V
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	3.28 lbs
Electrostatic discharge protection	Yes
Surge protection	Yes

Finishing casing		
Material	Iron	
Color	Gray RAL 9006	
Process	Powder coating	

Finishing diffuser		
Material	PE	
Color	neutral	

Finishing mounting frame		
Material	Iron	
Color	Gray RAL 9006	
Process	Powder coating	

	Notes:	
-		

Bond Pro



Bollard & Pole | 120-277 V | topLED 10.8 W | CRI 80 | 4000K | General Lighting | Gray RAL 9006 | Wet location | 120V/277V + 0-10V interface | Base **LL-E81101-N-00**


Single emission bollard & pole for outdoor application. The natural white LED light source with a general lighting light distribution is composed of 18 topled LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 1460 lm, with a 135.2 lm/W nominal luminous efficacy.


The device body is made of iron and features a grey ral 9006 finish, processed by means of coating; the diffuser is made of pe; the mounting frame is made of iron, with a grey ral 9006 finish, processed by means of coating. The ingress protection degree is IP65; the total weight is of 3.285 lbs.

The total absorbed power is W.

and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





Energy efficiency class

This product contains a light source of energy efficiency class E.

Led features	
Light Output Ratio (LOR)	42 %
Source lumens	1460 lm
Delivered lumens	627 lm
Power	12 W
Luminaire efficacy	52 lm/W
Color temperature	4000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Color rendering index	80 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25
LED Life / Failure Ratio	
L70 B20 C0 72500h	

UGR	
UGR axial	17.5
UGR transversal	17.9
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL		
Light distribution symmetry	Symmetrical 2	
C0/C180 optics	106°	
C90/C270 optics	102°	

Bond_Pro



Bond_Pro | Bollard & Pole | Accessories LL-E81101-N-00



Anchor

installation position: land,Cover material: pc

Code

E14931