Eyelet65_Q

Project: Type:



Projectors | 1 x powerLED 2.0 W | CRI 80 | 3500K | Wide Flood | Embossed white RAL 9003 | Damp location | 630mA LL-E97336-T-60







Technical data		
Туре	Surface	
Installation position	Wall lights - Ceiling - Floor	
Installation environment	Indoor	
Light Source	LED	
Optics	Wide Flood	
Light emission direction	frontal	
Power	2 W	
Operation	630mA	
Source lumens	249 lm	
ССТ	3500 K	
Color rendering index	80 Ra	
Safety class	Class 2	
IP	IP40	
IK	IK03	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	Yes	
Dimmable article	No	
Directional	Swivelling	
total angle (vertical plane)	180 °	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	Yes	
Cable length	3.28 ft	
Resin potting	No	
Type of light emission	Single emission	
Net weight	0.4 lbs	
Electrostatic discharge protection	No	
Surge protection	No	
Product technological characteristics	TVS	
Ordinary temperature on the glass	104 °F	

Aluminum 6026	
Embossed white RAL 9003	
Powder coating	
Aluminum 5754	
Anodized Black	
15 µm Anodizing	
tion	
No	
	_
	_
	_
·	
	Embossed white RAL 9003 Powder coating Aluminum 5754 Anodized Black 15 µm Anodizing

Eyelet65_Q



Projectors | 1 x powerLED 2.0 W | CRI 80 | 3500K | Wide Flood | Embossed white RAL 9003 | Damp location | 630mA

LL-E97336-T-60

Single emission projectors for indoor application. The 3500 LED light source with a wide flood light distribution is composed of 1 powerled LEDs with CCT of 3500 K and a CRI 80; the source luminous flux is 249 lm, with a 124.5 lm/W nominal luminous efficacy.

The device body is made of aluminium 6026 and features a embossed white ral 9003 finish, processed by means of powder coating. The ingress protection degree is IP40; the total weight is of 0.397 lbs.

The total absorbed power is 2 W. The power supply cable is included and features a 3.281 ft lenght.

and can be wall lights, ceiling or floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class E.

Led features	
Source lumens	249 lm
Color temperature	3500 K
Standard Deviation of Colour Matching	1/16 ANSI BIN
Color rendering index	80 Ra
Black Body Locus	On
LED Life / Failure Ratio	
L70 B10 C0 361980h (at Tj 60 Ta 25)	

COLOR VECTOR GRAPHIC

