


Eyelet65_R

Project: _____
Type: _____



Projectors | 1 x powerLED 2.0 W | CRI 80 | 3500K | Spot | Embossed white RAL 9003 |
Damp location | 630mA
LL-E96984-T-15



Technical data	
Type	Surface
Installation position	Wall lights - Ceiling - Floor
Installation environment	Indoor
Light Source	LED
Optics	Spot
Light emission direction	frontal
Power	2 W
Operation	630mA
Source lumens	249 lm
CCT	3500 K
Color rendering index	80 Ra
Safety class	Class 2
IP	IP40
IK	IK03
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	Yes
Dimmable article	No
Directional	Swivelling
total angle (vertical plane)	180 °
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	3.28 ft
Resin potting	No
Type of light emission	Single emission
Net weight	0.18 lbs
Electrostatic discharge protection	No
Surge protection	No
Product technological characteristics	TVS
Ordinary temperature on the glass	104 °F

Finishing casing

Material	Aluminum 6026
Color	Embossed white RAL 9003
Process	Powder coating

Finishing bracket

Material	Aluminum 5754
Color	Anodized Black
Process	15 µm Anodizing

Cables Electrification

Cable connector	No
-----------------	----

Notes:



Projectors | 1 x powerLED 2.0 W | CRI 80 | 3500K | Spot | Embossed white RAL 9003 |
 Damp location | 630mA
LL-E96984-T-15

Single emission projectors for indoor application. The 3500 LED light source with a spot light distribution is composed of 1 powered LEDs with CCT of 3500 K and a CRI 80; the source luminous flux is 249 lm, with a 124.5 lm/W nominal luminous efficacy.

The device body is made of aluminium 6026 and features a embossed white ral 9003 finish, processed by means of powder coating. The ingress protection degree is IP40; the total weight is of 0.176 lbs.

The total absorbed power is 2 W. The power supply cable is included and features a 3.281 ft lenght.

and can be wall lights, ceiling or floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class E.

Led features

Source lumens	249 lm
Color temperature	3500 K
Standard Deviation of Colour Matching	1/16 ANSI BIN
Color rendering index	80 Ra
Black Body Locus	On

LED Life / Failure Ratio

L70 B10 C0 361980h (at Tj 60 Ta 25)

COLOR VECTOR GRAPHIC

