Eyelet65_Q

Project: Type:




Projectors | 1 x powerLED 2 W | CRI 80 | 2700K | Flood | Embossed white RAL 9003 | Wet location | 630mA





LL-E91217-M-30





Technical data	
Туре	Surface
Installation position	Wall lights - Ceiling - Floor
Installation environment	Outdoor
Light Source	LED
Optics	Flood
Light emission direction	frontal
Power	2 W
Operation	630mA
Source lumens	219 lm
ССТ	2700 K
Color rendering index	80 Ra
Safety class	Class 2
IP	IP65
IK	IK03
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	Yes
Dimmable article	No
Directional	Swivelling
total angle (vertical plane)	180 °
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	3.28 ft
Resin potting	No
Type of light emission	Single emission
Net weight	0.4 lbs
Electrostatic discharge protection	No
Surge protection	No
Product technological characteristics	TVS
Ordinary temperature on the glass	104 °F
	•

Finishing casing			
Material	Aluminum 6026		
Color	Embossed white RAL 9003		
Process	Open pore anodizing + Powder Coating		
Finishing diffuser			
Material	Extra clear glass		
Color	transparent		
Finishing bracket			
Material	Aluminum 5754		
Color	Anodized Black		
Process	15 μm Anodizing		
Cables Electrifica	tion		
Cable connector	No		

ı	Notes:			
_				
_				

Eyelet65_Q



Projectors | 1 x powerLED 2 W | CRI 80 | 2700K | Flood | Embossed white RAL 9003 | Wet location | 630mA | Base

LL-E91217-M-30


Single emission projectors for outdoor application. The super warm LED light source with a flood light distribution is composed of 1 powerled LEDs with CCT of 2700 K and a CRI 80; the source luminous flux is 219 lm, with a 109.5 lm/W nominal luminous efficacy.


The device body is made of aluminium 6026 and features a embossed white ral 9003 finish, processed by means of open pore anodizing + powder coating; the diffuser is made of extra clear glass. The ingress protection degree is IP65; the total weight is of 0.397 lbs.

The total absorbed power is 2 W. The power supply cable is included and features a 3.281 ft lenght.

and can be wall lights, ceiling or floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





Energy efficiency class

This product contains a light source of energy efficiency class D.

Led features	
Light Output Ratio (LOR)	69 %
Source lumens	219 lm
Delivered lumens	152 lm
Power	2 W
Luminaire efficacy	76 lm/W
Color temperature	2700 K
Standard Deviation of Colour Matching	1.5 Step
Color rendering index	80 Ra
LED Life / Failure Ratio	
L70 B10 C0 361980h (at Tj 60 Ta 25)	

UGR	
UGR axial	24.3
UGR transversal	24.3
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Light distribution symmetry	Symmetrical
C0/C180 optics	27°

Eyelet65_Q



Eyelet65_Q | Projectors | Accessories LL-E91217-M-30

Anchor installation position: land,Cover material: aisi 304 steel	Code E98624
Anchor installation position: land,Cover material: aisi 304 steel	Code E98669
Anti-glare Anti-glare Type: snoot. Material:Pom-C, color:Matt Black.	Code E99746