Eyelet65_Q

Project: Type:

Finishing casing



Projectors | 1 x powerLED 2 W | CRI 80 | 4000K | Spot | Embossed white RAL 9003 | Wet location | 630mA LL-E91217-N-15







Technical data		
Туре	Surface	
Installation position	Wall lights - Ceiling - Floor	
Installation environment	Outdoor	
Light Source	LED	
Optics	Spot	
Light emission direction	frontal	
Power	2 W	
Operation	630mA	
Source lumens	249 lm	
ССТ	4000 K	
Color rendering index	80 Ra	
Safety class	Class 2	
IP	IP65	
IK	IK03	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	Yes	
Dimmable article	No	
Directional	Swivelling	
total angle (vertical plane)	180 °	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	Yes	
Cable length	3.28 ft	
Resin potting	No	
Type of light emission	Single emission	
Net weight	0.4 lbs	
Electrostatic discharge protection	No	
Surge protection	No	
Product technological characteristics	TVS	
Ordinary temperature on the glass	104 °F	

1	180°
0.9	1.3

Material	Aluminum 6026
Color	Embossed white RAL 9003
Process	Open pore anodizing + Powder Coating
Finishing diffuser	
Material	Extra clear glass
Color	transparent
Finishing bracket	
Material	Aluminum 5754
Color	Anodized Black
Process	15 μm Anodizing
Cables Electrifica	tion
Cable connector	No

No	tes:			

Eyelet65_Q



Projectors | 1 x powerLED 2 W | CRI 80 | 4000K | Spot | Embossed white RAL 9003 | Wet location | 630mA | Base

LL-E91217-N-15


Single emission projectors for outdoor application. The natural white LED light source with a spot light distribution is composed of 1 powerled LEDs with CCT of 4000 K and a CRI 80; the source luminous flux is 249 lm, with a 124.5 lm/W nominal luminous efficacy.


The device body is made of aluminium 6026 and features a embossed white ral 9003 finish, processed by means of open pore anodizing + powder coating; the diffuser is made of extra clear glass. The ingress protection degree is IP65; the total weight is of 0.397 lbs.

The total absorbed power is 2 W. The power supply cable is included and features a 3.281 ft lenght.

and can be wall lights, ceiling or floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





Energy efficiency class

This product contains a light source of energy efficiency class D.

Led features	
Light Output Ratio (LOR)	73 %
Source lumens	249 lm
Delivered lumens	182 lm
Power	2 W
Luminaire efficacy	91 lm/W
Color temperature	4000 K
Standard Deviation of Colour Matching	1.5 Step
Color rendering index	80 Ra
LED Life / Failure Ratio	
L 70 B10 C0 361980h (at Ti 60 Ta 25)	

L70 B10 C0 361980h (at Tj 60 Ta 25)	
	_

UGR	
UGR axial	24.8
UGR transversal	24.4
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL		
Light distribution symmetry	Symmetrical 2	
C0/C180 optics	18°	
C90/C270 optics	23°	

Eyelet65_Q



Eyelet65_Q | Projectors | Accessories LL-E91217-N-15

Anchor installation position: land,Cover material: aisi 304 steel	Code E98624
Anchor installation position: land,Cover material: aisi 304 steel	Code E98669
Anti-glare Anti-glare Type: snoot. Material:Pom-C, color:Matt Black.	Code E99746