llamt66

Project: Type:



Wall Lights | 1 x powerLED 2 W | CRI 80 | 2700K | Flood | Embossed white RAL 9003 | Wet location | 630mA





LL-E97086-M-30



Ø 0.8	
	2

0.9

Technical data		
	Semi-recessed	
Type		
Installation position	Wall lights	
Installation environment	Indoor - Outdoor	
Light Source	LED	
Optics	Flood	
Light emission direction	downward	
Power	2 W	
Operation	630mA	
Source lumens	219 lm	
CCT	2700 K	
Color rendering index	80 Ra	
Safety class	Class 2	
IP	IP66	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	Yes	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	Yes	
Cable length	3.28 ft	
Resin potting	Yes	
Type of light emission	Single emission	
Net weight	0.38 lbs	
Electrostatic discharge protection	No	
Surge protection	No	
Product technological characteristics	TVS	
Ordinary temperature on the glass	104 °F	

Finishing casing				
Material	OT58 brass			
Color	Embossed white RAL 9003			
Process	Powder coating			
Cables Electrifica	tion			
Cable connector	No			
Notes:				

Ilamt66



Wall Lights | 1 x powerLED 2 W | CRI 80 | 2700K | Flood | Embossed white RAL 9003 | Wet location | 630mA

LL-E97086-M-30

Single emission wall lights for indoor or outdoor application. The super warm LED light source with a flood light distribution is composed of 1 powerled LEDs with CCT of 2700 K and a CRI 80; the source luminous flux is 219 lm, with a 109.5 lm/W nominal luminous efficacy.

The device body is made of ot58 brass and features a embossed white ral 9003 finish, processed by means of powder coating. The ingress protection degree is IP66; the total weight is of 0.384 lbs.

The total absorbed power is 2 W. The power supply cable is included and features a 3.281 ft lenght.

and can be wall lights-mounted, with a 0.945 in diameter hole (in plasterboard) with an outer casing, code E84349(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class D.

Led features	
Source lumens	219 lm
Color temperature	2700 K
Standard Deviation of Colour Matching	1.5 Step
Color rendering index	80 Ra
LED Life / Failure Ratio	
L70 B10 C0 361980h (at Tj 60 Ta 25)	

llamt66



Ilamt66 | Wall Lights | Accessories LL-E97086-M-30



Outer casing

Type of installation: masonry L=1.65in, H=1.18in, D=1.18in

Code

E84349