
llamt66	Project:	<u> </u>
	Туре:	

Wall Lights | 1 x powerLED 2 W | CRI 80 | 3000K | Wide Flood | Embossed white RAL 9003 | Wet location | 630mA LL-E97086-W-60



Technical data		
Туре	Semi-recessed	
Installation position	Wall lights	
Installation environment	Indoor - Outdoor	
Light Source	LED	
Optics	Wide Flood	
Light emission direction	downward	
Power	2 W	
Operation	630mA	
Source lumens	233 lm	
ССТ	3000 K	
Color rendering index	80 Ra	
Safety class	Class 2	
IP	IP66	
Glow wire test	850°	
Direct mounting on normally flammable surfaces	Yes	
CE	Yes	
ETL	Yes	
Dimmable article	No	
Directional	No	
Tilting	No	
Walk-over	No	
Drive-over	No	
Cable included	Yes	
Cable length	3.28 ft	
Resin potting	Yes	
Type of light emission	Single emission	
Net weight	0.38 lbs	
Electrostatic discharge protection	No	
Surge protection	No	
Product technological characteristics	TVS	
Ordinary temperature on the glass	104 °F	



 (\mathbb{D})

0.9

Finishing casi	ng
Material	OT58 brass
Color	Embossed white RAL 9003
Process	Powder coating

Cables Electrification

No

Cable connector

Notes:

llamt66

Wall Lights | 1 x powerLED 2 W | CRI 80 | 3000K | Wide Flood | Embossed white RAL 9003 | Wet location | 630mA | Base LL-E97086-W-60

Single emission wall lights for indoor or outdoor application. The warm white LED light source with a wide flood light distribution is composed of 1 powerled LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 233 lm, with a 116.5 lm/W nominal luminous efficacy.

The device body is made of ot58 brass and features a embossed white ral 9003 finish, processed by means of powder coating. The ingress protection degree is IP66; the total weight is of 0.384 lbs.

The total absorbed power is 2 W. The power supply cable is included and features a 3.281 ft lenght.

and can be wall lights-mounted, with a 0.945 in diameter hole (in plasterboard) with an outer casing, code E84349(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.


Energy efficiency class


This product contains a light source of energy efficiency class D.

ed features	
ight Output Ratio (LOR)	86 %
Source lumens	233 lm
Delivered lumens	202 lm
Power	2 W
uminaire efficacy	101 lm/W
olor temperature	3000 K
tandard Deviation of Colour Matching	1.5 Step
Color rendering index	80 Ra
ED Life / Failure Ratio	
70 B10 C0 361980h (at Tj 60 Ta 25)	

28.7
28.5
S=0.25H
70/50/20

OPTICAL				
Light distribution symmetry	Symmetrical 2			
C0/C180 optics	69°			
C90/C270 optics	73°			





C0/C180 (Half-peak divergence: 69.2°) C90/C270 (Half-peak divergence: 72.6°)

Ilamt66 | Wall Lights | Accessories LL-E97086-W-60



Outer casing Type of installation: masonry L=1.65in, H=1.18in, D=1.18in **Code** E84349