llamt66

Project: Type:



Wall Lights | 1 x powerLED 2 W | CRI 80 | 2700K | Wide Flood | Embossed white RAL 9003 | Wet location | 630mA



0.9

LL-E97086-M-60

Technical data

Surge protection

Product technological characteristics

Ordinary temperature on the glass



□ 1.2

Туре	Semi-recessed
Installation position	Wall lights
Installation environment	Indoor - Outdoor
Light Source	LED
Optics	Wide Flood
Light emission direction	downward
Power	2 W
Operation	630mA
Source lumens	219 lm
ССТ	2700 K
Color rendering index	80 Ra
Safety class	Class 2
IP	IP66
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	Yes
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	3.28 ft
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.38 lbs
Electrostatic discharge protection	No

Finishing codes				
Finishing casing	OTF0 b			
Material	OT58 brass			
Color	Embossed white RAL 9003			
Process	Powder coating			
Cables Electrification				
Cable connector	No			
Cable connector Notes:	No			
	No			

2

No

TVS

104 °F

Ilamt66



Wall Lights | 1 x powerLED 2 W | CRI 80 | 2700K | Wide Flood | Embossed white RAL 9003 | Wet location | 630mA

LL-E97086-M-60

Single emission wall lights for indoor or outdoor application. The super warm LED light source with a wide flood light distribution is composed of 1 powerled LEDs with CCT of 2700 K and a CRI 80; the source luminous flux is 219 lm, with a 109.5 lm/W nominal luminous efficacy.

The device body is made of ot58 brass and features a embossed white ral 9003 finish, processed by means of powder coating. The ingress protection degree is IP66; the total weight is of 0.384 lbs.

The total absorbed power is 2 W. The power supply cable is included and features a 3.281 ft lenght.

and can be wall lights-mounted, with a 0.945 in diameter hole (in plasterboard) with an outer casing, code E84349(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class D.

Led features		
Source lumens	219 lm	
Color temperature	2700 K	
Standard Deviation of Colour Matching	1.5 Step	
Color rendering index	80 Ra	
LED Life / Failure Ratio		
L70 B10 C0 361980h (at Tj 60 Ta 25)		

llamt66



Ilamt66 | Wall Lights | Accessories LL-E97086-M-60



Outer casing

Type of installation: masonry L=1.65in, H=1.18in, D=1.18in

Code

E84349