llamt66

Project: Type:

Finishing casing

Material



Wall Lights | 1 x powerLED 2 W | CRI 80 | 2700K | Narrow Spot | Embossed white RAL 9003 | Wet location | 630mA









Ø 0.8	
	2

OT58 brass

0.9

Technical data	
Type	Semi-recessed
Installation position	Wall lights
Installation environment	Indoor - Outdoor
Light Source	LED
Optics	Narrow Spot
Light emission direction	downward
Power	2 W
Operation	630mA
Source lumens	219 lm
ССТ	2700 K
Color rendering index	80 Ra
Safety class	Class 2
IP	IP66
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	Yes
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	3.28 ft
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.38 lbs
Electrostatic discharge protection	No
Surge protection	No
Product technological characteristics	TVS
Ordinary temperature on the glass	104 °F

Color	Embossed white RAL 9003	
Process	Powder coating	
Cables Electrifica	tion	
Cable connector	No	
Notes:		

Ilamt66



Wall Lights | 1 x powerLED 2 W | CRI 80 | 2700K | Narrow Spot | Embossed white RAL 9003 | Wet location | 630mA

LL-E97086-M-08

Single emission wall lights for indoor or outdoor application. The super warm LED light source with a narrow spot light distribution is composed of 1 powerled LEDs with CCT of 2700 K and a CRI 80; the source luminous flux is 219 lm, with a 109.5 lm/W nominal luminous efficacy.

The device body is made of ot58 brass and features a embossed white ral 9003 finish, processed by means of powder coating. The ingress protection degree is IP66; the total weight is of 0.384 lbs.

The total absorbed power is 2 W. The power supply cable is included and features a 3.281 ft lenght.

and can be wall lights-mounted, with a 0.945 in diameter hole (in plasterboard) with an outer casing, code E84349(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class D.

Led features	
Source lumens	219 lm
Color temperature	2700 K
Standard Deviation of Colour Matching	1.5 Step
Color rendering index	80 Ra
LED Life / Failure Ratio	
L70 B10 C0 361980h (at Tj 60 Ta 25)	

llamt66



Ilamt66 | Wall Lights | Accessories LL-E97086-M-08



Outer casing

Type of installation: masonry L=1.65in, H=1.18in, D=1.18in

Code

E84349