




Wall Lights | 1 x powerLED 1.0 W | CRI 80 | 3500K | Asymmetric Wallwasher | Embossed white RAL 9003 | Damp location | 350mA  
**LL-E93508-T-07**



### Technical data

Type	Encasement with flange
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Optics	Asymmetric Wallwasher
Light emission direction	downward
Power	1 W
Operation	350mA
Source lumens	107 lm
CCT	3500 K
Color rendering index	80 Ra
Safety class	Class 2
IP	IP44
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	Yes
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	3.28 ft
Resin potting	Yes
Type of light emission	Single emission
Net weight	0.26 lbs
Electrostatic discharge protection	No
Surge protection	No
Ordinary temperature on the glass	104 °F

### Finishing casing

Material	Aluminum 6026
Color	Embossed white RAL 9003
Process	Powder coating

### Finishing diffuser

Material	UV Resistant Polycarbonate
Color	transparent

### Cables Electrification

Cable connector	No
-----------------	----

### Notes:

---



---



---



---



Wall Lights | 1 x powerLED 1.0 W | CRI 80 | 3500K | Asymmetric Wallwasher | Embossed white RAL 9003 | Damp location | 350mA

**LL-E93508-T-07**

Single emission wall lights for indoor application. The 3500 LED light source with a asymmetric wallwasher light distribution is composed of 1 powerled LEDs with CCT of 3500 K and a CRI 80; the source luminous flux is 107 lm, with a 107.0 lm/W nominal luminous efficacy.

The device body is made of aluminium 6026 and features a embossed white ral 9003 finish, processed by means of powder coating; the diffuser is made of uv resistant polycarbonate. The ingress protection degree is IP44; the total weight is of 0.265 lbs.

The total absorbed power is 1 W. The power supply cable is included and features a 3.281 ft lenght.

and can be wall lights-mounted, with a 0.787 in diameter hole (in plasterboard) with an outer casing, code E98950(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

#### Energy efficiency class

This product contains a light source of energy efficiency class E.

#### Led features

Source lumens	107 lm
Color temperature	3500 K
Standard Deviation of Colour Matching	1/16 ANSI BIN
Color rendering index	80 Ra

#### LED Life / Failure Ratio

L70 B10 C0 197960h (at Tj 60 Ta 25 )



Laella\_R | Wall Lights | Accessories  
**LL-E93508-T-07**

Outer casing

Type of installation: masonry L=1.22in, H=0.83in, D=0.83in.

Material: Polyamide, color: black.

**Finish**

Black

**Code**

E98950