

OP2132 – ZUME™
16" – Catenary



Type: Project:

VisaLighting.com/products/Zume

Fill in shaded boxes using information listed below

Order Code: **OP2132**
MODEL

A SOURCE – **MVOLT**
VOLTAGE

B FINISH

C CATENARY OPTION

D DIFFUSER OPTION

E PCL (POWER CORD LENGTH)



MSC option shown

This pure glowing sphere appears to be floating in space and is crowned with a unique cap. An ideal addition to a patio, courtyard or boulevard. Offered in two sizes in frosted or white acrylic. The decorative cap can be finished with any of our 16 standard paint finishes.

DIMENSIONS

DIA = Diameter X = Body Height PCL = Power Cord Length
EPA = Effective Projected Area


E ⚠ Power cord length must be specified.

PCL is the distance (in inches) from the fixture to the end of the cord jacket or to the end of installed quick connect (for options including a quick connect)
Example: PCL (60) indicates a power cord length of 60".

DIA 16" (406 mm)
X 16-1/4" (413 mm)
PCL 60" (1524 mm)

X value changes with options
MSC add 1-3/4"

EPA: 2.4ft²
WEIGHT 9 lbs.



A SOURCE (Select one) and VOLTAGE

MVOLT fixture accepts 120 through 277 input voltage
0-10V dimmable to 1%. 83CRI, within 3-step MacAdam

Sources	CCT	Delivered Lumens		Power (watts)	Voltage
		White Globe	Frosted Globe		
L30K-L	3000K	1300	1600	17	MVOLT
L35K-L	3500K	1300	1600		
L40K-L	4000K	1300	1600		
L30K-H	3000K	2000	2400	28	
L35K-H	3500K	2100	2500		
L40K-H	4000K	2100	2500		

B FINISH (Select one)

See page 4 for color chart

Powder Coat Painted Finishes (Standard)

AG7038 Agate Grey	GLIM Glimmer	PB1035 Pearl Beige
BMAT Bronze Matte	GSIL Graphite Silver	RUST Rust
BRNZ Bronze	GW9002 Grey White	SUNG Sungold
BSIL Blade Silver	HTHR Heather	TW9016 Traffic White
CVBL Cove Blue	JB9005 Jet Black	
CW9001 Cream	OBRZ Old Bronze	

C CATENARY OPTION (Select one)


See page 2 for catenary option illustrations

1QC One quick connect (factory installed)
2QC Two quick connects (factory installed)
MSC Mid-run horizontal splice connection (mounted at top of unit)
SPC Single power cord

D DIFFUSER OPTION

Globe is white if no option is selected

FRST Frosted translucent globe



White

Frosted Translucent



IP65



LED



ETL Listed



5 Year Warranty


OP2132 – ZUME
16" – Catenary




Catenary Option Illustrations

See page 3 for additional accessories


Splice Connect




Quick Connect
(Factory Installed)



Photometrics



Frosted Globe




White Globe

Technical Information

- High or low lumen output
- Integral driver
- IP65 rated
- **Stainless steel structural cables are not included. Structural cables and their connections to their structures are to be designed by a qualified structural engineer**
- Cables connecting fixtures to each other are considered to be structural
- Primary cable connection to the fixture accepts a 1/8" to 1/4" diameter cable
- Fixture must be suspended if the catenary cable design is greater than 1/4" diameter
- Crossing secondary cable is perpendicular to the primary cable and is limited to 1/8" when the primary cable is 1/4"
- Black power cord
- White acrylic diffuser or optional frosted translucent acrylic diffuser
 - ◆ UV stable
 - ◆ UL-94 HB Flame Class rated
- Spun aluminum cap with laser cut-outs; cast aluminum mounting component
- No VOC powder coat paint finish
- Tested to ANSI C136.31 'American National Standard for Roadway and Area Lighting Equipment' at or above 3G vibration levels for 100,000 cycles in X, Y, Z axes
- ETL listed for wet locations

Relative Scale Drawing



OP2132 – ZUME
16"-Catenary




For important information about accessory applications, see "Catenary Design Guide."
For technical specifications and installation information, see "Installation Instructions"

ACCESSORIES (Order Separately)


Power Connection Accessories

**Quick Connect Jumper Cord
(AY-QC7P6-X)**



Qty (1) per sku
X = cord length (in feet)
4 standard lengths
AY-QC7P6-1
AY-QC7P6-5
AY-QC7P6-10
AY-QC7P6-25
Custom lengths available
upon request

**Power Cord
(AY-P6-50)**




Black cord, 50 feet per sku
Custom lengths available
upon request

**Power Cord Ties
(AY-WT-100)**




Qty (100) per sku

**Liquid Tite Cord Grip
(AY-CG)**




Qty (1) per sku

**Quick Connectors
(AY-QC7SET)**



(1) plug, (1) socket per sku

**Quick Connect 3-way splitter
(AY-QC3S)**



Power Control - up to 3 fixtures
Qty (1) per sku

Catenary Suspension Accessories

**3/32" Stainless Steel Cable
(AY-CBL1/8-50)**



50 feet per sku

**Stainless Steel
Compression Sleeve
(AY-CS1/8)**




Qty (10) per sku

**Stainless Steel U-Bolts
(AY-UBX/X)**



Qty (1) per sku
X/X = catenary cable diameter
5 sizes
AY-UB3/16
AY-UB1/4
AY-UB3/8
AY-UB1/2
AY-UB5/8

**Mounting Bracket
(AY-BRKT)**



(1) stainless steel bracket with (2)
washers, (2) #10, 1.5" screws
per sku

Accessories are made for Visa Lighting catenary applications. If sourced elsewhere, materials must be of equivalent grade.

