

OP2142 – ZUME™

20" – Catenary



Type:

Project:

VisaLighting.com/products/Zume
Order Code: **OP2142**

MODEL

A SOURCE- **MVOLT**

VOLTAGE

B FINISH**C** CATENARY OPTION**D** DIFFUSER OPTION**E** PCL (POWER CORD LENGTH)

Fill in shaded boxes using information listed below



MSC option shown

This pure glowing sphere appears to be floating in space and is crowned with a unique cap. An ideal addition to a patio, courtyard or boulevard. Offered in two sizes in frosted or white acrylic. The decorative cap can be finished with any of our 16 standard paint finishes.

DIMENSIONS

DIA = Diameter X = Body Height PCL = Power Cord Length
EPA = Effective Projected Area

E Power cord length must be specified.


PCL is the distance (in inches) from the fixture to the end of the cord jacket or to the end of installed quick connect (for options including a quick connect)

Example: PCL (60) indicates a power cord length of 60".

DIA 20" (508 mm)
X 20-1/4" (514 mm)
PCL 60" (1524 mm)

X value changes with options
MSC add 1-3/4"

EPA: 3.6ft²
WEIGHT 10 lbs.



A SOURCE (Select one) and VOLTAGE

MVOLT fixture accepts 120 through 277 input voltage
0-10V dimmable to 1%. 82CRI, within 3-step MacAdam

Sources	CCT	Delivered Lumens		Power (watts)	Voltage
		White Globe	Frosted Globe		
L30K-L	3000K	1400	1600	27	MVOLT
L35K-L	3500K	1500	1700		
L40K-L	4000K	1500	1700		
L30K-H	3000K	1800	2100	37	
L35K-H	3500K	1900	2100		
L40K-H	4000K	1900	2200		

B FINISH (Select one)

See page 4 for color chart

Powder Coat Painted Finishes (Standard)

AG7038	Agate Grey	GLIM	Glimmer	PB1035	Pearl Beige
BMAT	Bronze Matte	GSIL	Graphite Silver	RUST	Rust
BRNZ	Bronze	GW9002	Grey White	SUNG	Sungold
BSIL	Blade Silver	HTHR	Heather	TW9016	Traffic White
CVBL	Cove Blue	JB9005	Jet Black		
CW9001	Cream	OBRZ	Old Bronze		

C CATENARY OPTION (Select one)

See page 2 for catenary option illustrations

1QC	One quick connect (factory installed)
2QC	Two quick connects (factory installed)
MSC	Mid-run horizontal splice connection (mounted at top of unit)
SPC	Single power cord

D DIFFUSER OPTION

Globe is white if no option is selected

FRST Frosted translucent globe


White



Frosted Translucent



IP65



LED



ETL Listed



5 Year Warranty

OP2142 – ZUME


20" – Catenary



Catenary Option Illustrations


See page 3 for additional accessories

Splice Connect




Quick Connect


(Factory Installed)



Photometrics



Frosted Globe




White Globe

Technical Information

- High or low lumen output
- Integral driver
- IP65 rated
- Stainless steel structural cables are not included. Structural cables and their connections to their structures are to be designed by a qualified structural engineer**
- Cables connecting fixtures to each other are considered to be structural
- Primary cable connection to the fixture accepts a 1/8" to 1/4" diameter cable
- Fixture must be suspended if the catenary cable design is greater than 1/4" diameter
- Crossing secondary cable is perpendicular to the primary cable and is limited to 1/8" when the primary cable is 1/4"
- Black power cord
- White acrylic diffuser or optional frosted translucent acrylic diffuser
 - UV stable
 - UL-94 HB Flame Class rated
- Spun aluminum cap with laser cut-outs; cast aluminum mounting component
- No VOC powder coat paint finish
- Tested to ANSI C136.31 'American National Standard for Roadway and Area Lighting Equipment' at or above 3G vibration levels for 100,000 cycles in X, Y, Z axes
- ETL listed for wet locations

Relative Scale Drawing



OP2142 – ZUME

20" Catenary




For important information about accessory applications, see "Catenary Design Guide."
For technical specifications and installation information, see "Installation Instructions"

ACCESSORIES (Order Separately)


Power Connection Accessories

Quick Connect Jumper Cord
(AY-QC7P6-X)



Qty (1) per sku
X = cord length (in feet)
4 standard lengths
AY-QC7P6-1
AY-QC7P6-5
AY-QC7P6-10
AY-QC7P6-25
Custom lengths available
upon request

Power Cord
(AY-P6-50)




Black cord, 50 feet per sku
Custom lengths available
upon request

Power Cord Ties
(AY-WT-100)




Qty (100) per sku

Liquid Tite Cord Grip
(AY-CG)




Qty (1) per sku

Quick Connectors
(AY-QC7SET)



(1) plug, (1) socket per sku

Quick Connect 3-way splitter
(AY-QC3S)



Power Control - up to 3 fixtures
Qty (1) per sku

Catenary Suspension Accessories

3/32" Stainless Steel Cable
(AY-CBL1/8-50)



50 feet per sku

Stainless Steel
Compression Sleeve
(AY-CS1/8)




Qty (10) per sku

Stainless Steel U-Bolts
(AY-UBX/X)



Qty (1) per sku
X/X = catenary cable diameter
5 sizes
AY-UB3/16
AY-UB1/4
AY-UB3/8
AY-UB1/2
AY-UB5/8

Mounting Bracket
(AY-BRKT)



(1) stainless steel bracket with (2)
washers, (2) #10, 1.5" screws
per sku

Accessories are made for Visa Lighting catenary applications. If sourced elsewhere, materials must be of equivalent grade.

[illegible]


Painted Finishes (Standard)

TW9016
Traffic White (RAL9016)

CW9001
Cream (RAL9001)



GW9002
Grey White (RAL9002)



JB9005
Jet Black (RAL9005)



AG7038
Agate Grey (RAL7038)



HTHR
Heather




CVBL
Cove Blue




BSIL
Blade Silver



GSIL
Graphite Silver



GLIM
Glimmer



SUNG
Sungold



BRNZ
Bronze



OBRZ
Old Bronze



BMAT
Bronze Matte



PB1035
Pearl Beige (RAL1035)



RUST
Rust

800-788-VISA