

**Application**

This LED wall luminaire has a directed light distribution designed for general illumination of pathways and building entrances from various mounting heights.

**Materials**

Luminaire housing constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 Clear safety glass  
 Reflector made of pure anodized aluminum  
 Silicone applied robotically to casting, plasma treated for increased adhesion  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 64  
 Weight: 1.0lbs

**Electrical**

Operating voltage 120-277V AC  
 Minimum start temperature -20° C  
 LED module wattage 3.2W  
 System wattage 5W  
 Controllability 0-10V dimmable  
 Color rendering index Ra > 80  
 Luminaire lumens 145 lumens (3000K)  
 LED service life (L70) 60,000 hours

**LED color temperature**

- 4000K - Product number + **K4 (EXPRESS)**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3 (EXPRESS)**
- 2700K - Product number + **K27**
- Amber - Product number + **AMB**

**Wildlife friendly amber LED - Optional**

Luminaire is optionally available with a narrow bandwidth, amber LED source (585-600nm) approved by the FWC. This light output is suggested for use within close proximity to sea turtle nesting and hatching habitats. Electrical and control information may vary from standard luminaire.


LED module wattage 2.1 W (Amber)  
 System wattage 2.9W (Amber)  
 Luminaire lumens 81 lumens (Amber)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors    Black (BLK)            White (WHT)            RAL:  
                                  Bronze (BRZ)            Silver (SLV)            CUS :



**LED wall luminaire · directed light**

	LED	A	B	C
<b>33 539</b> <b>ADA</b>	3.2W	3	5 1/8	3 1/4

Type:  
 BEGA Product:  
 Project:  
 Modified:

