

Application

The LED wall mounted luminaire has light output on two sides. Arranged individually or in groups, this is a great design element for a host of lighting applications.

Materials

Luminaire housing constructed of die-cast and extruded marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
 Matte safety glass
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP65
 Weight: 11.7 lbs

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30°C
 LED module wattage 9.6W
 System wattage 13W
 Controllability 0-10V dimmable
 Color rendering index $Ra > 80$
 Luminaire lumens 598 lumens (3000K)
 Lifetime at $T_a = 15^{\circ}\text{C}$ $> 500,000$ h (L70)
 Lifetime at $T_a = 50^{\circ}\text{C}$ 212,000 h (L70)

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



LED wall luminaire · light output on two sides

	LED	A	B	C	Required wiring box
44 436	9.6W	24 3/8	4 1/8	5	19 537

Type:
 BEGA Product:
 Project:
 Modified:

