

**Application**

The LED wall mounted luminaire has light output on two sides. Arranged individually or in groups, this is a great design element for a host of lighting applications.

**Materials**

Luminaire housing constructed of die-cast and extruded marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
 Matte safety glass  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP65  
 Weight: 28 lbs

**Electrical**

Operating voltage 120-277VAC  
 Minimum start temperature  $-30^{\circ}\text{C}$   
 LED module wattage 30.4 W  
 System wattage 36 W  
 Controllability 0-10V dimmable  
 Color rendering index  $Ra > 80$   
 Luminaire lumens 1646 lumens (3000K)  
 Lifetime at  $T_a = 15^{\circ}\text{C}$   $> 500,000$  h (L70)  
 Lifetime at  $T_a = 45^{\circ}\text{C}$  229,000 h (L70)

**LED color temperature**

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



**LED wall luminaire - light output on two sides**

	LED	A	B	C	Required wiring box
<b>44 438</b>	30.6 W	59 7/8"	4 1/8"	5"	<b>19 537</b>

Type:  
 BEGA Product:  
 Project:  
 Modified:

