

Multiple pole tops for 3 floodlights

Multiple pole tops for multiple configuration of floodlights on BEGA poles. Ready for installation for 3 floodlights.


Pole top made of extruded and die cast aluminum. The pole top slip fits a 3" O.D. diameter pole and is secured to the pole by eight (8) stainless steel set screws. Cannot be used on standard BEGA poles with tenons, consult factory for custom pole options. Floodlights are attached to the cross beam with a rotatable, die cast aluminum, clamping plate with two M8 screws for attachment of the floodlight yoke. The plates can be rotated around the pole top in 90° increments and have a 1/2" threaded cord seal for floodlight cable entry. Floodlights can be rotated 360° on the clamping plate. Removable, fully gasketed, cover plates are provided for access inside the cross beam.

All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

Note: Consideration must be given by the designer/specifier to assure the adequacy of pole design to safely support the wind load of pole top with floodlights. Light pole design requires consideration of field conditions such as (but not limited to) wind zone, height, and loading. BEGA is not responsible with compatibility for use with poles by others.

Note: This accessory is for use with BEGA yoke mounted large scale floodlights.

Type:
 BEGA Product:
 Project:
 Voltage:
 Color:
 Options:
 Modified:



		Pole top	Insert depth	A	B	EPA
70763	Pole top for 3 floodlights	Ø3"	5 7/8	69 1/2	7 11/16	1.5