


Linear

LiNi-R XL RGB Fixture Guide

KKDÖ

Indoor | Recessed | RGB output




Key applications

- ✓ Ceiling
- ✓ Interior
- ✓ Orientation lighting
- ✓ Special effect

Key features

- ✓ Custom lengths
- ✓ Diffusion: Homogenous
- ✓ Direct view
- ✓ Form factor: Medium
- ✓ IP40
- ✓ RGB



Linear

LiNi-R XL RGB

Specification sheet



Dimension	H27.9/W31/L99.3-2016mm (H1.1/W1.22/L3.91-79.37in) (excluding spring clips)
PCB increment	83.3mm increment/2000mm max (3.28in increment/78.74in max)
LED pitch	13.9mm - 72LED/m (0.55in - 22LED/ft)
Chip	Red TEKCORE/Green EPILEDS/Blue 3E
Beam angle	110° (Diffused Cover)
Colours	Red 620-625nm/Blue 455-460nm/Green 520-525nm
Bin/Step	5nm tolerance
CRI	N/A
Lifetime	50,000 hours @ 25°C (50,000 hours @ 77°F)
Operating temp	T _a = -25 to 55°C (T _c max = 66.5°C) T _a = -13 to 131°F (T _c max = 151.7°F)
IP rating	IP40
Finish	Silver anodised
Cover/lens	Diffused
Mounting	Recessed mounting via spring clip
Power feed	Hardwire tails or male/female connectors
Control	DMX/DALI





PERFORMANCE DATA

Power consumption	Supply voltage	Supply current
15.6W/m (4.75W/ft)	24V DC	0.65A/m (0.20A/ft)

Diffused Cover

Red: 61lm/m (19lm/ft)
 Green: 132lm/m (40lm/ft)
 Blue: 22lm/m (7lm/ft)
 RGB: 192lm/m (59lm/ft)



Data derived from IESNA LM-79-08 accredited testing of production samples.

Linear

LiNi-R XL RGB

Code Table



FIXTURE

Model	Finish	Cover	Grade	LED	Colour (CCT)	Length Availability ¹	IP	Cable Length	Power Feed ²	Input									
LiNi-R XL	RX	Silver Anodised	SA	Diffused	C	s	501	RGB	RGB	m	99.3-2016mm 83.3mm increments	IP40	40	300mm/11.81"	0300	Single no sheath tail	S00X	DC 24V	g
						i					3.91-79.37in 3.28in increments			1000mm/39.37"	1000	Double no sheath tail	D00X		
											(Specify length code OR total run length)					Single no sheath IP20 connector	S20X		
																Double no sheath IP20 connector	D20X		

¹ Refer to **Length Availability List** or enter total run length instead of length code

² Refer to **Power Feed Options** on **Options** pages

Code Example:

RX	-	SA	-	C	-	s	-	501	-	RGB	-	m	-	516	-	40	-	0300	-	D00X	-	g
LiNi-R XL		Silver Anodised		Diffused				501		RGB		m		515.8mm		IP40		300mm/11.81"		Double no sheath tail		DC 24V

ACCESSORIES

Connection Accessories

KKCN-07	4 PIN RGB male & female 50mm/1.97" pair
KKCN-09	4 PIN RGB male & female 300mm/11.81" pair
KKCN-11	4 PIN RGB 300mm/11.81" extension lead

PSU/Driver

DALI/DMX
* Refer to Driver/PSU Options page for details or provide requirement and KKDC to offer the suitable option

* Refer to **Power feed** on **Accessories** pages

LED ENGINE VARIANTS (LED STRIP TYPE)

Colour	Output	LED	Lumen/m	Lumen/ft	W/m	W/ft	Spec Doc	Length	Increment
Single CCT	Low	352	190	59	5.5	1.67	LiNi-R XL 352	99.3-2016mm (3.91-79.37in)	83.3mm (3.28in)
	Low	504	510	155	12.5	3.81	LiNi-R XL 504	116-2016mm (4.57-79.37in)	100mm (3.94in)
	Mid	508	710	216	17.5	5.33	LiNi-R XL 508	87.4-2016mm (3.44-79.37in)	71.4mm (2.81in)
	Max	040	2000	610	40	12.2	LiNi-R XL A040	93-1516mm (3.66-59.68in)	38.46mm (1.51in)
Warm Dim/Dynamic White	Low	207	350	105	10.95	3.34	LiNi-R XL 207	99.3-2016mm (3.91-79.37in)	83.3mm (3.28in)
	Mid	208	630	213	15.6	4.75	LiNi-R XL 208	182.7-2016mm (7.19-79.37in)	166.7mm (6.56in)
RGB		501	Red 61 Green 132 Blue 22 RGB 192	Red 19 Green 40 Blue 7 RGB 59	15.6	4.75	LiNi-R XL RGB	99.3-2016mm (3.91-79.37in)	83.3mm (3.28in)

* Performance data: diffused cover, RGB

LiNi-R XL RGB


Length Availability List

Length Code		Fixture Length ¹		LED Strip ²		End Cap Dimension ³		Wattage (W)	Output (lm)			
Metric	Imperial(US)	Metric	Imperial(US)	Metric	Imperial(US)	Metric	Imperial(US)		R	G	B	W
m0099	i0004	99mm	3.91in	83mm	3.28in	11mm	0.43in	1.30	2	3	1	5
m0183	i0007	183mm	7.19in	167mm	6.56in	11mm	0.43in	2.60	3	7	1	10
m0266	i0010	266mm	10.47in	250mm	9.84in	11mm	0.43in	3.90	5	10	2	15
m0349	i0014	349mm	13.75in	333mm	13.12in	11mm	0.43in	5.20	6	13	2	20
m0433	i0017	433mm	17.04in	417mm	16.41in	11mm	0.43in	6.50	8	17	3	25
m0516	i0020	516mm	20.32in	500mm	19.69in	11mm	0.43in	7.80	10	20	4	30
m0599	i0024	599mm	23.60in	583mm	22.97in	11mm	0.43in	9.10	11	23	4	34
m0683	i0027	683mm	26.88in	667mm	26.25in	11mm	0.43in	10.40	13	27	5	39
m0766	i0030	766mm	30.16in	750mm	29.53in	11mm	0.43in	11.70	14	30	5	44
m0849	i0033	849mm	33.44in	833mm	32.81in	11mm	0.43in	13.00	16	33	6	49
m0933	i0037	933mm	36.72in	917mm	36.09in	11mm	0.43in	14.30	17	37	6	54
m1016	i0040	1016mm	40.00in	1000mm	39.37in	11mm	0.43in	15.60	19	40	7	59
m1099	i0043	1099mm	43.28in	1083mm	42.65in	11mm	0.43in	16.90	21	43	8	64
m1183	i0047	1183mm	46.57in	1167mm	45.94in	11mm	0.43in	18.20	22	47	8	69
m1266	i0050	1266mm	49.85in	1250mm	49.22in	11mm	0.43in	19.50	24	50	9	74
m1349	i0053	1349mm	53.13in	1333mm	52.50in	11mm	0.43in	20.80	25	53	9	79
m1433	i0056	1433mm	56.41in	1417mm	55.78in	11mm	0.43in	22.10	27	57	10	84
m1516	i0060	1516mm	59.69in	1500mm	59.06in	11mm	0.43in	23.40	29	60	11	89
m1599	i0063	1599mm	62.97in	1583mm	62.34in	11mm	0.43in	24.70	30	63	11	93
m1683	i0066	1683mm	66.25in	1667mm	65.62in	11mm	0.43in	26.00	32	67	12	98
m1766	i0070	1766mm	69.53in	1750mm	68.90in	11mm	0.43in	27.30	33	70	12	103
m1849	i0073	1849mm	72.81in	1833mm	72.18in	11mm	0.43in	28.60	35	73	13	108
m1933	i0076	1933mm	76.10in	1917mm	75.47in	11mm	0.43in	29.90	36	77	13	113
m2016	i0079	2016mm	79.38in	2000mm	78.75in	11mm	0.43in	31.20	38	80	14	118

¹ Actual total overall length of light fixture (LED strip + end caps + void/wire hole)

² Actual length of PCB strip

³ Actual length of 2x end caps







LiNi-R XL RGB Options



COVER/LENS OPTIONS

* Options are an integral part of the fixture ordering codes. Please refer to **Code Table** pages.




C Diffused cover


W31/H27.9mm (W1.22/H1.10")

POWER FEED OPTIONS


0300 S00X 300mm (11.81") Single no sheath tail




0300 D00X 300mm (11.81") Double no sheath tail




0300 S20X 300mm (11.81") Single no sheath IP20 connector




0300 D20X 300mm (11.81") Double no sheath IP20 connector




1000 S00X 1000mm (39.37") Single no sheath tail




1000 D00X 1000mm (39.37") Double no sheath tail



1000 S20X 1000mm (39.37") Single no sheath IP20 connector



1000 D20X 1000mm (39.37") Double no sheath IP20 connector



Key

Control Gear Power supply, sub-controllers & control systems

JB Junction box / cable connection


Linear

LiNi-R XL RGB Options





POWER FEED OPTIONS (CONTINUED)

4 Pin RGB Female Connector





4 Pin RGB Male Connector




POWER FEED

Note: Accessories are to be ordered separately with corresponding code shown below.



KKCN-07 50mm (1.97in) pair
KKCN-09 300mm (11.81in) pair
4 PIN RGB male + female
connector set



KKCN-11
4 PIN RGB 300mm (11.81in)
extension lead

KKDC CONTROL

IP20
Plastic housing
L170/W59/H29mm
(L6.69/W2.32/H1.14in)

KKDM-06 1-10V
visDIM dimmable sub-controller
(4 x 8A max @ 12-36V)



IP20
Plastic housing
L170/W53.4/H28mm
(L6.69/W2.10/H1.10in)

KKSC-05 DMX
visDIM dimmable sub-controller
(4 x 5A max @ 12-36V)



IP20
Plastic housing
L170/W59/H29mm
(L6.69/W2.32/H1.14in)

KKDL-02 DALI
visDIM dimmable sub-controller
(4 x 8A max @ 12-36V)



IP20
Plastic housing
L166/W53.4/H23mm
(L6.54/W2.10/H0.91in)

KKDL-03 DALI
visDIM dimmable sub-controller
(4 x 5A max @ 12-36V)

AVAILABLE PSU OPTIONS

Control Mode	PSU (Order Code)	Input Voltage AC	Output Voltage DC	Rated Output Current	Rated Power	Dim %	IP Rating
Switched	CEN-60-24	90-295V	24V	2.5A	60W	-	IP67
	HLG-60H-24	90-305V	24V	2.5A	60W	-	IP67
	HLG-100H-24	90-305V	24V	4.0A	100W	-	IP67
	HLG-150H-24	90-305V	24V	6.3A	150W	-	IP67
	HLG-240H-24	90-305V	24V	10A	240W	-	IP67
0-10V (1-10V)	PWM-40-24	90-305V	24V	1.67A	40W	100-0.15 (100-10)	IP67
	PWM-60-24	90-305V	24V	2.5A	60W	100-0.15 (100-10)	IP67
	PWM-90-24	90-305V	24V	3.67A	90W	100-0.15 (100-10)	IP67
	PWM-120-24	90-305V	24V	5.0A	120W	100-0.15 (100-10)	IP67
DALI	LIN100A1	120-277V	24V	1A per channel	100W	100-0.1	IP66/IP40
DMX RGB	LIN100A1	120-277V	24V	1.33A per channel	100W	100-0.1	IP66/IP40
DMX RGBW	LIN100A1	120-277A	24V	1A per channel	100W	100-0.1	IP66/IP40

Flicker Free Options - Combination of PSU+ sub-controller

Control Mode	PSU (Order Code)	Sub-controller (Order Code)	Input Voltage AC	Output Voltage DC	Rated Output Current	Rated Power	Dim %	IP Rating PSU/ Sub-controller
0-10V or 1-10V	CEN-60-24	KKDM-06	90-295V	24V	2.5A	60W	100-0.9	IP67/IP20
	HLG-60H-24	KKDM-06	90-295V	24V	2.5A	60W	100-0.9	IP67/IP20
	HLG-100H-24	KKDM-06	90-295V	24V	4.0A	100W	100-0.9	IP67/IP20
	HLG-150H-24	KKDM-06	90-295V	24V	6.3A	150W	100-0.9	IP67/IP20
	HLG-240H-24	KKDM-06	90-295V	24V	10.0A	240W	100-0.9	IP67/IP20
DALI	CEN-60-24	KKDL-02/03	90-295V	24V	2.5A	60W	100-0.1	IP67/IP20
	HLG-60H-24	KKDL-02/03	90-305V	24V	2.5A	60W	100-0.1	IP67/IP20
	HLG-100H-24	KKDL-02/03	90-305V	24V	4.0A	100W	100-0.1	IP67/IP20
	HLG-150H-24	KKDL-02/03	90-305V	24V	6.3A	150W	100-0.1	IP67/IP20
	HLG-240H-24	KKDL-02/03	90-305V	24V	10.0A	240W	100-0.1	IP67/IP20
DMX RGB	CEN-60-24	KKSC-05	90-295V	24V	2.5A	60W	100-0.9	IP67/IP20
	HLG-60H-24	KKSC-05	90-305V	24V	2.5A	60W	100-0.9	IP67/IP20
	HLG-100H-24	KKSC-05	90-305V	24V	4A	100W	100-0.9	IP67/IP20
	HLG-150H-24	KKSC-05	90-305V	24V	6.3A	150W	100-0.9	IP67/IP20
	HLG-240H-24	KKSC-05	90-305V	24V	10.0A	240W	100-0.9	IP67/IP20

¹ The items shown above cover the most frequently used specification but does not exhaust the possible options

² PSU and/or driver can be chosen from the table, or KKDC may recommend the best option upon receipt of the controls requirement and installation environment

³ Electrical shop drawing will include detailed information of PSU and relevant control drivers

⁴ Cut sheets are available on the controls section of www.kkdc.lighting or upon request