

MAGNETA Outdoor
3-728-xx

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-15 Black





-16 Gray



-22 Oiled Bronze

- LIGHT SOURCE** 1 x 12.1W LED, 3000K, CRI 90
- LUMINAIRE POWER** 14.7W at 120V
- RATED LIFE** 60000 hr RL
- OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K
- LUMEN OUTPUT** Delivered: 735 lm (LM-79)
- INPUT VOLTAGE** 120V to 277V AC, 50/60Hz
- DRIVER OUTPUT** 350mA, 14.7W max power
- DIMMING** TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 1% current output
- CONSTRUCTION** Cast Aluminum and Glass
- DIFFUSER** - White Opal Glass
- FINISHES** Black (-15), Gray (-16), Oiled Bronze (-22)
- MOUNTING** 4" Octagonal J-Box *
* Deep J-Box (Required to house driver)
(Installer must provide a bead of caulk between fixture housing and mounting surface)
- STANDARDS** UL Wet listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

- W:** 4.75"
- H:** 14.50"
- Ext:** 3.50"
- M.C:** 10.98" From top of fixture

Order example for standard fixture:

3-728-22 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120V to 277V

Order example for optional color temperatures: **3-728-2722**

27: 2700K, **35:** 3500K, **40:** 4000K

