ACADIA Pendant

3-6142-xx



FIXTURE TYPE	LOCATION
PROJECT	DATE





-24 Satin Nickel

LIGHT SOURCE LED Array, 3000K, CRI 90

LUMINAIRE POWER 75.6W at 120V **RATED LIFE** 50000 hr RL

OPTIONAL COLOR

TEMPERATURES 3000K Only

LUMEN OUTPUT Delivered: 2500 lm (LM-79)

INPUT VOLTAGE 120V AC, 50/60Hz

DRIVER OUTPUT 24Vdc Constant Voltage, 3.2A max current

DIMMING TRIAC Dimming (Forward Phase, Magnetic Low Voltage)

CONSTRUCTION Cold Rolled Steel Housing and Canopy

DIFFUSER - Matte White Acrylic

FINISHES Satin Nickel (-24), Aged Brass (-40)

MOUNTING 4" Octagonal J-Box

STANDARDS ETL Damp listed, Conforms to UL STD 1598,

Certified CAN/CSA STD C22.2 No 250.0.

DIMENSIONS

Dia. Canopy: 6.69" W. Fixture: 25.00" 15.25" H. Fixture:

Supplied with 2-8", 2-12", and 3-16" stems to customize hanging height

Note: Canopy swivel allows up to a 22° slope

Order example for standard fixture: 3-6142-40 (x- Voltage - xxx-Sequence # - xx-Finish) 3: 120V Only



