

# ALTAIR Ceiling Mount

## 3-332-xx

oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-6 White



-15 Black



-22 Oiled Bronze



-24 Satin Nickel

**LIGHT SOURCE** 1 x 10.5W LED with Driver on board, 3000K, CRI 90

**LUMINAIRE POWER** 10.9W at 120V

**RATED LIFE** 30000 hr RL

**OPTIONAL COLOR TEMPERATURES** 3000K Only

**LUMEN OUTPUT** Delivered: 480 lm (LM-79)

**INPUT VOLTAGE** 120V AC, 60Hz

**DRIVER OUTPUT** N/A

**DIMMING** TRIAC Dimming



**CONSTRUCTION** Cast Aluminum Housing with Steel Backplate

**DIFFUSER** - Etched White Glass

**FINISHES** White (-6), Black (-15),  
Oiled Bronze (-22), Satin Nickel (-24)

**MOUNTING** 4" Octagonal J-Box

**STANDARDS** ETL Damp listed, Conforms to UL STD 1598,  
Certified CAN/CSA STD C22.2 No 250.0.



**DIMENSIONS**

**W:** 5.00"

**L:** 5.00"

**H:** 1.00"

Order example for standard fixture:

**3-332-22** (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120V Only

