

ECHO Ceiling Mount
3-694-xx-EM

oxygen

FIXTURE TYPE _____

LOCATION _____



PROJECT _____

DATE _____



-24 Satin Nickel

LIGHT SOURCE	2 x 10.1W LED, 3000K, CRI 90
LUMINAIRE POWER	25.7W at 120V
RATED LIFE	60000 hr RL
LUMEN OUTPUT	Delivered: 1277 lm (LM-79)
INPUT VOLTAGE	120V to 277V AC, 50/60Hz
DRIVER OUTPUT	700mA, 29.4W
DIMMING	TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 10% current output
CONSTRUCTION	Plated Steel and Acrylic / Fabric
DIFFUSER	- White Grass and Matte White Acrylic
FINISHES	Satin Nickel (-24)
MOUNTING	4" Octagonal J-Box
STANDARDS	ETL Dry/Damp listed, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS
Dia: 14.50"
H: 4.00"

EM Driver	Fullham HotspotLED Series
EM Battery Life	90 Minutes Minimum

Order example for standard fixture:
3-694-24-EM (x- Voltage - xxx-Sequence # - xx-Finish)
3: 120V to 277V

