

# AURORA Wall Sconce

## 3-551-xx

oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-24 Satin Nickel



-15 Black



-20 Polished Nickel

**LIGHT SOURCE** 1 x 8.2W LED, 3000K, CRI 90

**LUMINAIRE POWER** 10.1W at 120V

**RATED LIFE** 60000 hr RL

**OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K

**LUMEN OUTPUT** Delivered: 454 lm (LM-79)

**INPUT VOLTAGE** 120V to 277V AC, 50/60Hz

**DRIVER OUTPUT** 350mA, 14.7W max

**DIMMING** TRIAC and ELV dimming at 120V AC;  
0-10V dimming, 100% to 10% current output




**CONSTRUCTION** Plated Steel and Acrylic

**DIFFUSER** - Matte White Acrylic

**FINISHES** Black (-15), Polished Nickel (-20), Satin Nickel (-24)

**MOUNTING** 4" Octagonal J-Box\*  
4"x4" Square J-Box\* with single device mud ring  
\*Deep J-Box (Required to house driver)

**STANDARDS** UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598,  
Certified CAN/CSA, STD C22.2 No 250.0.



### DIMENSIONS

**Dia: 6.00"**

**Ext: 2.375"**

**M.C: 3.00" From Top of Fixture**

Order example for standard fixture:

**3-551-xx** (x-Voltage - xxx-Sequence # - xx-Finish)

Order example for optional color temperatures: **3-551-2724**

**27:** 2700K, **35:** 3500K, **40:** 4000K

