

**FUGIT Vanity**  
**3-5013-xx**

oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_


DATE \_\_\_\_\_



-15 Black



-20 Polished Nickel



-24 Satin Nickel

|                        |  |
|------------------------|--|
| <b>LIGHT SOURCE</b>    | 2 x 13W, 3000K CRI 90  |
| <b>LUMINAIRE POWER</b> | 32.9W at 120V  |
| <b>RATED LIFE</b>      | 60000 hr RL  |
| <b>LUMEN OUTPUT</b>    | Delivered: 2205 lm (LM-79)   |
| <b>INPUT VOLTAGE</b>   | 120V, 60Hz   |
| <b>DRIVER OUTPUT</b>   | 700mA, 30W max   |
| <b>DIMMING</b>         | TRIAC Dimming  |
| <b>CONSTRUCTION</b>    | Plated Steel and Acrylic   |
| <b>DIFFUSER</b>        | - Matte White Acrylic  |
| <b>FINISHES</b>        | Black (-15), Polished Nickel (-20), Satin Nickel (-24)   |
| <b>MOUNTING</b>        | 4" Octagonal J-Box*<br>4"x4" Square J-Box* with single device mud ring<br>*Deep J-Box (Required to house driver) |
| <b>STANDARDS</b>       | ETL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598,<br>Certified CAN/CSA, STD C22.2 No 250.0.           |



**DIMENSIONS**  
**W: 34.25"**  
**H: 4.50"**  
**Ext: 3.125"**  
**M.C: 2.25" From Top of Fixture**

Order example for standard fixture:  
**3-5013-xx** (x-Voltage - xxx-Sequence # - xx-Finish)

