

ATF7415-DTW

15W Dim-To-Warm LED Track Head Track Lighting

	Job Information	
Project Name		Туре
Location		
Quantity		Date
Contact/Phone		
Notes		

Features

Body

Constructed of aluminum, the body features an aesthetically pleasing smooth cylindrical shape. The body included a colour matching aluminum heat sink in order to provide maximum heat dissipation.

Beam Spread

The fixture is available in 38° beam angle.

Dimming

The integrated driver is dims the light to a warmer colour temperature when used with TRIAC / ELV dimming controls (Consult factory for compatible dimmers).

Adjustability

Adjustable up to 90° tilt and 330° rotation to allow for spotlight into multiple directions.

LED Characteristics

High powered 15W Sharp[®] GW6NGWJCS0C LED chip maintains uniform intensity with a typical luminous flux up to 1026 lumens, making it a suitable replacement for 55W PAR38 halogen and 22W PAR20 CMH lamps; with a CRI of 90+. Available in 2750 K (dimmable to 2000 K) correlated colour temperature.

Compatibility

Fixture is provided with A-Line connector which is compatible with Juno style track. For other connector configuration (Liteline, Halo), please contact your A-Line representative.

SPECIFICATION				
Application	Track			
Approved Location	Dry			
Beam Angle	38°			
ССТ	2750 K~2000 K			
Certification	cULus			
Colour	BK / WH			
CRI	90+			
Dimming	Yes			
Dimming Tech	TRIAC			
LM79	Yes			
LM80	Yes			
Lumens	1026			
Lumens per Watt	68.4			
Lumen Maintenance	70% @ 50,000 hrs			
Primary Voltage	120			
Rotation	330°			
Tilt	90°			
Warranty	3 Years			
Wattage	15			



Description

IIS

LISTED


ATF7415-HC

The ATF7415-DTW is a dim-to-warm 15W high powered LED track fixture specially designed for task and accent lighting. Available black and white finishes.


Notes: For additional options please consult your A-Line Lighting representative. Juno is a registered trademark of Juno Lighting Group. Halo is a registered trademark of Cooper Lighting. Lightolier is a registered trademark of

Philips. Due to our continued efforts to improve

our products, product specifications are subject to change without notice.







Liteline Corporation Copyright © 2019 All rights reserved. Telephone 416.996.1856 1.866.730.7704 Fax 905.709.5255 1.888.738.9736



Accessories

series. Available in black or white body. ATF7415-SN


ATF7415-SN Snoot accessory for ATF7415 series. Available in black or white body.

Honeycomb accessory for ATF7415

Photometry

ATF7415-DTW-38: 15W, Dim-To-Warm LED Track, 2750°K, 38° Beam Angle

Zonal I	nal Lumen Summary			
Zone	Lumens	% Luminaire		
0-30	877.4	85.5%		
0-40	962.5	93.8%		
0-60	1,011.0	98.5%		
60-90	15.0	1.5%		
0-90	1,026.1	100%		



Illuminance a Center Beam FC			at a Distance Beam Width		
2.0ft	637.3 fc			1.2 ft	1.2 ft
4.0ft	159.3 fc			2.5 ft	2.5 ft
6.0ft	70.8 fc			3.7 ft	3.7 ft
8.0ft -	39.8 fc			5.0 ft	5.0 ft
10.0ft	25.5 fc			6.2 ft	6.2 ft
	Vert. Spread: 34.5°		н	Horiz. Spread: 34.5°	