

|       |          |       |
|-------|----------|-------|
| DATE: | PROJECT: | TYPE: |
|-------|----------|-------|

CATALOG NUMBER LOGIC:



\*Lamp details available on the next page.

\*\*For use in Back Box installation only.

**CATALOG NUMBER LOGIC**

Example: B - SQ - MR - 359 - BLP - AJ - TP

**MATERIAL**

(Blank) - Aluminum B - Brass

**INSTALLATION**

(Blank) - Back Box

**SERIES**

SQ - Square Step Star

**SOURCE**

MR - MR16 Lamp

**LAMP TYPE**

0 - MR16 HALOGEN LAMP (Furnished by others)

MR16 LED (This choice requires lamp number selection)\*

**FINISH (See page 2 for full-color swatches)**

Standard Finishes (BZP, BZW, BLP, BLW, WHP, WHW, SAP, VER)

Premium Finish (ABP, AMG, AQW, BCM, BGE, BPP, CAP, CMG, CRI, CRM, HUG, MDS, NBP, OCP, RMG, SDS, SMG, TXF, WCP, WIR)

Also available in RAL Finishes



Brass Finishes (MAC, POL, MIT)

**OPTION**

AJ - Adjustable Lamp Bracket\*\*

TP - Thermal Protection (20W lamp max.)\*\*

DATE: \_\_\_\_\_ PROJECT: \_\_\_\_\_ TYPE: \_\_\_\_\_




**STANDARD FINISHES**



[Click Here](#) to view larger, full-color swatches of all available finishes on our website.




**PREMIUM FINISHES**





By SORAA™

# MR16 LED LAMP

| <p><b>B-K Lamp # 359</b><br/>           Base: GU5.3 Bi-Pin<br/>           Input Voltage: 12V<br/>           CCT: 2700K<br/>           Beam: 10° Spot</p>         | <p>Mfg. #: MR16-<br/>           SM16-07-10D-827-H1<br/>           Wattage: 7.5W<br/>           Lamp Efficacy: 77 (Lm/W)<br/>           Rated Life: 35,000 hrs</p> | <p>CBCP (cd): 8000<br/>           CRI: &gt;90<br/>           Power Factor: 0.92<br/>           Dimmable: Yes<br/>           Lumens: 575</p> |  <table border="1"> <thead> <tr> <th>Distance feet</th> <th>Beam Dia. (50% CBCP)</th> <th>Footcandles</th> </tr> </thead> <tbody> <tr><td>3'</td><td>0.5'</td><td>634</td></tr> <tr><td>6'</td><td>1.0'</td><td>160</td></tr> <tr><td>9'</td><td>1.6'</td><td>69</td></tr> <tr><td>12'</td><td>2.1'</td><td>40</td></tr> <tr><td>15'</td><td>2.6'</td><td>23</td></tr> </tbody> </table>   | Distance feet | Beam Dia. (50% CBCP) | Footcandles | 3' | 0.5' | 634 | 6' | 1.0' | 160 | 9' | 1.6' | 69 | 12' | 2.1' | 40 | 15' | 2.6' | 23 |
|--|---|---|---|---------------|----------------------|-------------|----|------|-----|----|------|-----|----|------|----|-----|------|----|-----|------|----|
| Distance feet  | Beam Dia. (50% CBCP)  | Footcandles   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 3'   | 0.5'  | 634   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 6'   | 1.0'  | 160   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 9'   | 1.6'  | 69  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 12'  | 2.1'  | 40  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 15'  | 2.6'  | 23  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| <p><b>B-K Lamp # 361</b><br/>           Base: GU5.3 Bi-Pin<br/>           Input Voltage: 12V<br/>           CCT: 2700K<br/>           Beam: 25° Narrow Flood</p> | <p>Mfg. #: MR16-<br/>           SM16-07-25D-827-H1<br/>           Wattage: 7.5W<br/>           Lamp Efficacy: 80 (Lm/W)<br/>           Rated Life: 35,000 hrs</p> | <p>CBCP (cd): 3170<br/>           CRI: &gt;90<br/>           Power Factor: 0.92<br/>           Dimmable: Yes<br/>           Lumens: 600</p> |  <table border="1"> <thead> <tr> <th>Distance feet</th> <th>Beam Dia. (50% CBCP)</th> <th>Footcandles</th> </tr> </thead> <tbody> <tr><td>3'</td><td>1.3'</td><td>251</td></tr> <tr><td>6'</td><td>2.7'</td><td>63</td></tr> <tr><td>9'</td><td>4.0'</td><td>27</td></tr> <tr><td>12'</td><td>5.3'</td><td>16</td></tr> <tr><td>15'</td><td>6.7'</td><td>9</td></tr> </tbody> </table>     | Distance feet | Beam Dia. (50% CBCP) | Footcandles | 3' | 1.3' | 251 | 6' | 2.7' | 63  | 9' | 4.0' | 27 | 12' | 5.3' | 16 | 15' | 6.7' | 9  |
| Distance feet  | Beam Dia. (50% CBCP)  | Footcandles   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 3'   | 1.3'  | 251   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 6'   | 2.7'  | 63  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 9'   | 4.0'  | 27  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 12'  | 5.3'  | 16  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 15'  | 6.7'  | 9   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| <p><b>B-K Lamp # 362</b><br/>           Base: GU5.3 Bi-Pin<br/>           Input Voltage: 12V<br/>           CCT: 2700K<br/>           Beam: 36° Flood</p>        | <p>Mfg. #: MR16-<br/>           SM16-07-36D-827-H1<br/>           Wattage: 7.5W<br/>           Lamp Efficacy: 80 (Lm/W)<br/>           Rated Life: 35,000 hrs</p> | <p>CBCP (cd): 1550<br/>           CRI: &gt;90<br/>           Power Factor: 0.92<br/>           Dimmable: Yes<br/>           Lumens: 600</p> |  <table border="1"> <thead> <tr> <th>Distance feet</th> <th>Beam Dia. (50% CBCP)</th> <th>Footcandles</th> </tr> </thead> <tbody> <tr><td>3'</td><td>1.9'</td><td>119</td></tr> <tr><td>6'</td><td>3.9'</td><td>30</td></tr> <tr><td>9'</td><td>5.8'</td><td>13</td></tr> <tr><td>12'</td><td>7.8'</td><td>7</td></tr> <tr><td>15'</td><td>9.7'</td><td>4</td></tr> </tbody> </table>     | Distance feet | Beam Dia. (50% CBCP) | Footcandles | 3' | 1.9' | 119 | 6' | 3.9' | 30  | 9' | 5.8' | 13 | 12' | 7.8' | 7  | 15' | 9.7' | 4  |
| Distance feet  | Beam Dia. (50% CBCP)  | Footcandles   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 3'   | 1.9'  | 119   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 6'   | 3.9'  | 30  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 9'   | 5.8'  | 13  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 12'  | 7.8'  | 7   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 15'  | 9.7'  | 4   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| <p><b>B-K Lamp # 363</b><br/>           Base: GU5.3 Bi-Pin<br/>           Input Voltage: 12V<br/>           CCT: 3000K<br/>           Beam: 10° Spot</p>         | <p>Mfg. #: MR16-<br/>           SM16-07-10D-830-H1<br/>           Wattage: 7.5W<br/>           Lamp Efficacy: 80 (Lm/W)<br/>           Rated Life: 35,000 hrs</p> | <p>CBCP (cd): 8400<br/>           CRI: &gt;90<br/>           Power Factor: 0.92<br/>           Dimmable: Yes<br/>           Lumens: 600</p> |  <table border="1"> <thead> <tr> <th>Distance feet</th> <th>Beam Dia. (50% CBCP)</th> <th>Footcandles</th> </tr> </thead> <tbody> <tr><td>3'</td><td>0.5'</td><td>666</td></tr> <tr><td>6'</td><td>1.0'</td><td>168</td></tr> <tr><td>9'</td><td>1.6'</td><td>72</td></tr> <tr><td>12'</td><td>2.1'</td><td>42</td></tr> <tr><td>15'</td><td>2.6'</td><td>24</td></tr> </tbody> </table> | Distance feet | Beam Dia. (50% CBCP) | Footcandles | 3' | 0.5' | 666 | 6' | 1.0' | 168 | 9' | 1.6' | 72 | 12' | 2.1' | 42 | 15' | 2.6' | 24 |
| Distance feet  | Beam Dia. (50% CBCP)  | Footcandles   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 3'   | 0.5'  | 666   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 6'   | 1.0'  | 168   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 9'   | 1.6'  | 72  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 12'  | 2.1'  | 42  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 15'  | 2.6'  | 24  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| <p><b>B-K Lamp # 365</b><br/>           Base: GU5.3 Bi-Pin<br/>           Input Voltage: 12V<br/>           CCT: 3000K<br/>           Beam: 25° Narrow Flood</p> | <p>Mfg. #: MR16-<br/>           SM16-07-25D-830-H1<br/>           Wattage: 7.5W<br/>           Lamp Efficacy: 84 (Lm/W)<br/>           Rated Life: 35,000 hrs</p> | <p>CBCP (cd): 3300<br/>           CRI: &gt;90<br/>           Power Factor: 0.92<br/>           Dimmable: Yes<br/>           Lumens: 630</p> |  <table border="1"> <thead> <tr> <th>Distance feet</th> <th>Beam Dia. (50% CBCP)</th> <th>Footcandles</th> </tr> </thead> <tbody> <tr><td>3'</td><td>1.3'</td><td>266</td></tr> <tr><td>6'</td><td>2.7'</td><td>67</td></tr> <tr><td>9'</td><td>4.0'</td><td>29</td></tr> <tr><td>12'</td><td>5.3'</td><td>17</td></tr> <tr><td>15'</td><td>6.7'</td><td>10</td></tr> </tbody> </table>  | Distance feet | Beam Dia. (50% CBCP) | Footcandles | 3' | 1.3' | 266 | 6' | 2.7' | 67  | 9' | 4.0' | 29 | 12' | 5.3' | 17 | 15' | 6.7' | 10 |
| Distance feet  | Beam Dia. (50% CBCP)  | Footcandles   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 3'   | 1.3'  | 266   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 6'   | 2.7'  | 67  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 9'   | 4.0'  | 29  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 12'  | 5.3'  | 17  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 15'  | 6.7'  | 10  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| <p><b>B-K Lamp # 366</b><br/>           Base: GU5.3 Bi-Pin<br/>           Input Voltage: 12V<br/>           CCT: 3000K<br/>           Beam: 36° Flood</p>        | <p>Mfg. #: MR16-<br/>           SM16-07-36D-830-H1<br/>           Wattage: 7.5W<br/>           Lamp Efficacy: 84 (Lm/W)<br/>           Rated Life: 35,000 hrs</p> | <p>CBCP (cd): 1650<br/>           CRI: &gt;90<br/>           Power Factor: 0.92<br/>           Dimmable: Yes<br/>           Lumens: 630</p> |  <table border="1"> <thead> <tr> <th>Distance feet</th> <th>Beam Dia. (50% CBCP)</th> <th>Footcandles</th> </tr> </thead> <tbody> <tr><td>3'</td><td>1.9'</td><td>125</td></tr> <tr><td>6'</td><td>3.9'</td><td>32</td></tr> <tr><td>9'</td><td>5.8'</td><td>14</td></tr> <tr><td>12'</td><td>7.8'</td><td>8</td></tr> <tr><td>15'</td><td>9.7'</td><td>5</td></tr> </tbody> </table>    | Distance feet | Beam Dia. (50% CBCP) | Footcandles | 3' | 1.9' | 125 | 6' | 3.9' | 32  | 9' | 5.8' | 14 | 12' | 7.8' | 8  | 15' | 9.7' | 5  |
| Distance feet  | Beam Dia. (50% CBCP)  | Footcandles   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 3'   | 1.9'  | 125   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 6'   | 3.9'  | 32  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 9'   | 5.8'  | 14  |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 12'  | 7.8'  | 8   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |
| 15'  | 9.7'  | 5   |   |               |                      |             |    |      |     |    |      |     |    |      |    |     |      |    |     |      |    |

**B-K LIGHTING**

MADE IN THE USA

559.438.5800 | INFO@BKLIGHTING.COM | BKLIGHTING.COM


THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF B-K LIGHTING, INC. AND ITS RECEIPT OR POSSESSION DOES NOT CONVEY ANY RIGHTS TO REPRODUCE, DISCLOSE ITS CONTENTS, OR TO MANUFACTURE, USE OR SELL ANYTHING IT MAY DESCRIBE. REPRODUCTION, DISCLOSURE OR USE WITHOUT SPECIFIC WRITTEN AUTHORIZATION OF B-K LIGHTING, INC. IS STRICTLY FORBIDDEN.

# SQUARE STEP STAR (MR16 LAMP - JUNCTION BOX)

IP65 RATED

|       |          |       |
|-------|----------|-------|
| DATE: | PROJECT: | TYPE: |
|-------|----------|-------|

ACCESSORIES (Configure separately)



TR Series

UPMRM

TRSS-75

## SPECIFICATIONS

|                         |   |  |
|-------------------------|---|--|
| ELECTRICAL              | WATTAGE   | 7.5W   |
|                         | WIRING  | Teflon® coated wire, 18AWG, 600V, 250° C rated and certified to UL 1659 standard.  |
|                         | TRANSFORMER   | For use with 12VAC remote transformer.   |
| PHYSICAL                | MATERIALS   | Furnished in copper-free aluminum (360) or brass (360).  |
|                         | BACKBOX   | Rectangular, 4-5/8" x 2-7/8" deep, cast aluminum construction. Front access for wire connection and inspection. Provided with five (5) 1/2" NPS tapped holes and two (2) plugs. Suitable for concrete pour.  |
|                         | FACEPLATE   | Cast construction with machined finish. Countersunk holes provide for flush hardware mounting with two (2) tamper-resistant, stainless steel mounting screws. Stainless steel universal mounting ring for faceplate adjustment and 1/8" thick HT-805A silicone foam gasket with acrylic adhesive for water-tight seal. |
|                         | LAMP  | For use with bi-pin MR16 lamps. Not for use with IR technology lamps. Halogen sourced by others.   |
|                         | INSTALLATION  | For use with 50W maximum lamp when installed into non-combustible materials or with 20W maximum lamp into combustible materials (Type Non IC) (requires optional thermal protection).  |
|                         | LENS  | Heat treated rectilinear lens provides wide lateral distribution and long forward throw.   |
|                         | AIMING & CONTROL  | 90° optical cutoff for mounting heights well below typical visual glare angles. Optional adjustable lamp bracket provides up to 24° vertical aiming, captive thumb screw and quick release bracket to maintain optical alignment during re-lamping.  |
|                         | SOCKET  | Specification grade, ceramic body, miniature bi-pin quartz lamp holder. GU5.3 base. Nickel alloy contacts and heat resistant, spring loaded, stainless steel lamp retaining clips.   |
|                         | FINISH  | StarGuard, our 15-stage chromate-free process cleans and conversion coats aluminum components prior to application of Class 'A' TGIC polyester powder coating and is RoHS compliant. Powder coat or metal finish options available for brass material and metal finish option only for stainless steel material.       |
|                         | WARRANTY  | 5-year limited warranty.   |
| CERTIFICATION & LISTING | ITL tested to IESNA LM-79. UL Listed. Certified to CAN/CSA/ANSI Standards. RoHS compliant. Suitable for indoor or outdoor use, in wet locations, and for installation in combustible materials (Type Non-IC) and within 4' of the ground. IP65 Rated. Made in the USA with sustainable processes. |  |



**B-K LIGHTING**

**MADE IN THE USA**

559.438.5800 | INFO@BKLIGHTING.COM | BKLIGHTING.COM