louis poulsen

LP CENTRUM

Designed by Kurt Nørregaard, Poul Henningsen



Description

The fixture provides 100% glare-free light. Its geometric design is based according to the mathematical lituus curve. All the illuminated surfaces are hit by the light at the same angle, casting the light into the room under the same conditions. This results in both horizontal and vertical light emission.

Variants

VARIANT NUMBER

COLOR, RAL
WHITE
WHITE

W / H / L (IN) / W (LB) 27.2 / 42.2 / 27.2 IN / 38.0 LB 27.2 / 42.2 / 27.2 IN / 38.0 LB

Materials & Finishes

MATERIALS

10000150713

Shades: Spun aluminum. Frame: Extruded, anodized aluminum. Suspension: Spun aluminum.

FINISHES

White, wet painted.

louis poulsen

Mounting

Suspension type: 1x PVC covered stainless steel aircraft cable. Canopy: White. Cord type: 3-conductor, 18 AWG white PVC power cord for MH or 5-conductor cord for LED light sources. Cord length: 12'. For mounting instructions, see download section on the product detail page.

Information

Electrical:

System Wattage: 36W LED Wattage: 33 W

Delivered lumens: 2,050 - 2,142 Efficacy: 56.9 lm/W - 59.5 lm/W

Certifications:

cULus, Damp Location Protection class IP20


Controllability: 0-10V Dimming

Color Rendering: Ra≥90 For the E-socket product variants, bulbs are not included. LED light


source is part of the product.

Light distribution diagrams


CARTESIAN



ISOLUX



POLAR



Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	LUMEN	FEATURES	CABLE
10000150712	LED 3000K 36W	120-277V/60HZ	2142	Dim 0-10v	Wht
10000150713	LED 2700K 36W	120-277V/60HZ	2050	Dim 0-10v	Wht

louis poulsen

Specification Notes

- a. MH light source only available with 120/204/240/277V core and coil ballast.
- b. Incandescent light source only available in 120V.
- c. LED light source only available with 120-277V electronic dimmable driver as standard.