
louis poulsen

AJ 50 WALL

Designed by Arne Jacobsen



Description

The fixture emits downward directed light. The shade is painted white on the inside to ensure a soft comfortable light distribution.

Variants

VARIANT NUMBER 5743909544 5743909557

5743909560

COLOR, RAL

BLK, 734 WHT, 044

NAT PAINT ALU, 162

W / H / L (IN) / W (LB)

13.8 / 9.8 / - IN / 4.2 LB 13.8 / 9.8 / - IN / 4.4 LB 13.8 / 9.8 / - IN / 4.2 LB

Materials & Finishes

MATERIALS

Back plate: Die cast aluminum. Shade: Die cast aluminum. LED enclosure: frosted glass.

FINISHES

Black, white or natural painted aluminum, textured powder coated.

Mounting

Surface: Mounted directly to finished surface over a 4" octagonal junction box. For mounting instructions, see download section on the product detail page.

louis poulsen

Information Electrical:

System Wattage: 9 W LED Wattage: 8 W Delivered lumens: 504 Im Efficacy: 56.0 Im/W Certifications: cULus, Wet Location Protection class IP65

IK class 06

BUG Rating: B0-U1-G0 Controllability: Phase dimming

Min.-Max. Ambient Temp: -30°C to +40°C

Color Rendering: Ra≥90 For the E-socket product variants, bulbs are not included. LED light


source is part of the product.

Light distribution diagrams


CARTESIAN




ISOLUX



POLAR



BUG



Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	LUMEN	FEATURES	CABLE
5743909544	LED 3000K 8.9W	120V	504	-	-
5743909557	LED 3000K 8.9W	120V	504	-	-
5743909560	LED 3000K 8.9W	120V	504	-	-