

Tadpole

inter•lux







Miniature IP66 adjustable and clamp bracket lockable exterior accent light. \emptyset 0.8" optics can be changed on site.

Materials:	Aluminum, toughened glass		
Color Temp:	2700K, 3000K, 3500K, or 4000K		
Lamp:	MSL Star (1 x Osram Oslon Square)		
IP rating:	IP66		
Optics:	0.8" \emptyset (20mm) optics. Please refer to the table below for beam angle options and ordering information.		
Finish:	White (Standard) Pure White RAL 9010 30% gloss Black (Standard) Powdercoat Matte Black 5% gloss Custom paint and anodized finishes available		
Dimming:	EldoLED 0-10V or DMX		
Supply:	Constant current remote driver required Allow 2W at 700mA		
Locking:	1.5mm Allen key required		
Available tilt:	±90°		
Weight:	0.44lb (0.2kg)		

Order Code	series.col temp.beam.finish.dimming	
Example	Tadpole.2700K.10°.white.D010	

Series	Color	Beam	Finish	Dimming and control
Tadpole	2700K 3000K 3500K 4000K	10° 13° 19° 35°	white black custom	D010 0-10V DMX DMX

LED Information

Each LED "lamp" consists of one or more Osram Oslon Square power LED thermally bonded to an aluminum cored printed circuit board.

MSL Star

0

Ø21mm PCB with a single Osram Oslon Square LED. For Ø20mm optics.



STOANE LIGHTING