

# Lux Beam

## 2" x 2" Track and Ceiling Beam Grid System

### Specifications/Features

#### Lux Beam

Lux Beam can be used to create a myriad of shapes and add people scale to any space. This system is ideal for floral areas or sit-down eating areas, anywhere you want to create a different feel to the space.

Easily installed. Features 120V/20A rated commercial grade ConTech track which includes an extensive selection of track fixtures. Aluminum extrusion may be suspended with threaded rod or cable.

Each Lux Beam section is supplied with the aluminum extrusion, track section (single or two circuit), mini live end (standard polarity) and mini live end (reverse polarity). System may also be used as a raceway.

Lux Beam dimensions are designed to allow for even one foot mounting, this includes connectors, beams and end piece.

Lux Beam is rated to support 85 lbs. per section supported by two (2) aircraft cable supports.

Product weight: 1.4LBS per linear foot.

#### Connectors and Accessories

All connectors can be used with power feed assemblies.

Connector weight: .8 - 1.25LBS each.

Maximum power rating is 2400 Watts: 20A at 120V, 60Hz. NEC allows 80% of full capacity or 1920 Watts.

#### Warranty


Lux Beam system is covered by ConTech's full one (1) year replacement guarantee after date of purchase.

#### Listing


cCSAus listed. Suitable for dry locations.

Lux Beam is approved for a maximum of 12 no. 12 AWG wires in wiring connectors.

Lux Beam is approved for mounting with two suspension points, mounted 12' apart.



2" X 2" Beam Section for Single or Two Circuit Track Section



2" X 2" Beam Section with Blank Filler Strip

### Track/Beam Ordering Information

Example Order  -

Track	Finish
<input type="text"/>	<input type="text"/>

#### 2" X 2" Beam Section with Single Circuit Track

- LB122-2** - 2" x 2" x 21.97" Beam with 20.11" Useable Track
- LB122-4** - 2" x 2" x 45.98" Beam with 44.13" Useable Track
- LB122-6** - 2" x 2" x 70.00" Beam with 68.11" Useable Track
- LB122-8** - 2" x 2" x 93.97" Beam with 92.13" Useable Track
- LB122-12** - 2" x 2" x 141.97" Beam with 140.12" Useable Track

- B** - Black
- P** - White
- S** - Silver

#### 2" X 2" Beam Section with Two Circuit Track

- LB222-2** - 2" x 2" x 21.97" Beam with 20.11" Useable Track
- LB222-4** - 2" x 2" x 45.98" Beam with 44.13" Useable Track
- LB222-6** - 2" x 2" x 70.00" Beam with 68.11" Useable Track
- LB222-8** - 2" x 2" x 93.97" Beam with 92.13" Useable Track
- LB222-12** - 2" x 2" x 141.97" Beam with 140.12" Useable Track

### Beam Ordering Information

Example Order  -

Beam	Finish
<input type="text"/>	<input type="text"/>

#### 2" X 2" Beam Section without Track


- LB22-2BL** - 2" x 2" x 21.97" Blank Beam Section with Blank Filler Strip
- LB22-4BL** - 2" x 2" x 45.98" Blank Beam Section with Blank Filler Strip
- LB22-6BL** - 2" x 2" x 70.00" Blank Beam Section with Blank Filler Strip
- LB22-8BL** - 2" x 2" x 93.97" Blank Beam Section with Blank Filler Strip
- LB22-12BL** - 2" x 2" x 141.97" Blank Beam Section with Blank Filler Strip

- B** - Black
- P** - White
- S** - Silver

# Lux Beam

## 2" x 2" Track and Ceiling Beam Grid System


### Connectors and Accessories



**End Connector**




LBC22-1-(B, P, S)



**T Connector**




LBC22-3-(B, P, S)



**Straight Connector**




LBC22-8-(B, P, S)



**90 Degree Connector**



LBC22-2-(B, P, S)



**X Connector**



LBC22-4-(B, P, S)



**Blank Top Cover, Decorative Element**




LBC22-24-(B, P, S) - 2' Top Cover  
 LBC22-48-(B, P, S) - 4' Top Cover  
 LBC22-72-(B, P, S) - 6' Top Cover  
 LBC22-96-(B, P, S) - 8' Top Cover

# Lux Beam

## 2" x 2" Track and Ceiling Beam Grid System

### Connectors and Accessories



**Aircraft Cable Set**

Includes cable coupler (threaded for 1/4-20 stud), cable holder with screw and washer, cable, 1/4-20 hanger bolt, junction box cross bar and 5" ceiling plate canopy.




- LBC22-10AC-(B, P, S)** - 10' Aircraft Cable Set with Canopy
- LBC22-20AC-(B, P, S)** - 20' Aircraft Cable Set with Canopy

**Power Feed Assembly**

Includes SJT power cord, 1/4-20 hanger bolt, acorn nut, junction box cross bar, tie wraps, strain relief grip and 5" ceiling plate canopy.



- LBC22-310PF-(B, P, S)** - 12/3 SJT, 10' Cord with Canopy
- LBC22-410PF-(B, P, S)** - 12/4 SJT, 10' Cord with Canopy
- LBC22-320PF-(B, P, S)** - 12/3 SJT, 20' Cord with Canopy
- LBC22-420PF-(B, P, S)** - 12/4 SJT, 20' Cord with Canopy



**Power Feed/Support Assembly**

Includes cable coupler (threaded for 1/4-20 stud), cable holder with screw and washer, SJT power cord, 1/4-20 hanger bolt, junction box cross bar, tie wraps, strain relief grip and 5" ceiling plate canopy.



- LBC22AC310PF-(B, P, S)** - 12/3 SJT, 10' Cord and Support Assembly with Canopy
- LBC22AC410PF-(B, P, S)** - 12/4 SJT, 10' Cord and Support Assembly with Canopy
- LBC22AC320PF-(B, P, S)** - 12/3 SJT, 20' Cord and Support Assembly with Canopy
- LBC22AC420PF-(B, P, S)** - 12/4 SJT, 20' Cord and Support Assembly with Canopy

12/4 Shown




**Safety Cable**

Steel, 18" safety cable for track fixtures. Secures with swivel snap.




- LA-25-SC** - 18" Cable

### Indirect Uplighting Accessories



Recessed Indirect Mounting Clips

Surface Indirect Mounting Clips



**Low Voltage Power Support for Indirect Uplighting**

Includes cable coupler, cable holder with screw and washer, 1/4-20 hanger bolt, junction box cross bar, tie wraps, strain relief grip, and 5" ceiling canopy. No power wires included. For plug-and-play, use tape light extensions. For hardwire, wires supplied by others. Finish: B, P, S



- LBC22AC310LV** - 10' Cord Support Assembly and Canopy




**Indirect End Cap Cover**

To cover both hardwire and plug-and-play connections. Not a structural component. Do not attach to support cable. Finish: P, S



- LBC22-COVER-(P,S)**



**Indirect Mounting Clips**

Four (4) mounting clips per package. 24" Spacing recommended between clips. For use with standard and double wide mounting channel. Refer to installation instructions for details. Finish: U



- LBC22-RC** - Recessed Clips
- LBC22-SC** - Surface Clips

Finish Codes: -B (Black), -P (White), -S (Silver)