

## 4108

120V-277V Universal Voltage

# Catalog #: Project: Date Prepared by:

### 1x4 LED Flat Panel





#### **DESCRIPTION**

Panel lights that are an economical, lightweight and easy to use that installs easily into standard lay-in grid ceilings. These panels are ready for use in a variety of both commercial and residential locations including kitchen, basements, office buildings, schools, garages and recreation rooms.

#### **DESIGN FEATURES**

#### Construction

- Heavy duty, white powder coated aluminum frame with hinged lens panel
- · Low-profile edge-lit design
- Damp listed

#### **Electrical**

- Optional SmartSensor Technology
- 120V-277V Universal Voltage
- Full range 0-10V dimming
- · IC rated for direct contact with insulation
- · Long-life LEDs and electrical driver
- 50,000 hour projected life
- Available 4000K CCT | 80 CRI
- 40W | 4400lms | 110lm/W
- Beam angle 114°

#### Installation

 Mounting hooks provide additional option for suspended chain or cable mount

#### Lens

 High performance lens is engineered to provide optimal lumen output with a uniform, glare-free distribution

#### Accessories (sold seperately)

- 4113HC Cable Hanging Kit
- 14FK 1x4 Flange Kit

#### Certifications

- · 5 year limited warranty
- UL Listed
- · DLC Qualified

ORDERING GUIDE		Example: 4108WH-SS-EM
Model #	Sensor Option	EM Option
4108WH		
4108WH	- blank : no SmartSensor - SS : SmartSensor	-blank : no EM -EM : add emergency option









