
# 8115HRA

120V-277V Universal Voltage

Catalog #:	Туре
Project:	Date
Prepared by:	

# 6" LED IC Airtight Remodel





### **DESCRIPTION**

An ideal solution for efficiency, safety, and flexible design aesthetics. The 8115HRA LED remodel housing is for use in shallow ceilings where 2"x8" joist constructions is used and can be in direct contact with ceiling insulation. This 8115HRA balances efficiency and cost to bring you the options needed to complete a variety of residential or commercial projects with a reliable and modern LED down light solution.

### **DESIGN FEATURES**

#### **Electrical**

- Voltage: 120V with 120V trimsVoltage: 277V with 277V trim
- Suitable for use in wet location and feed through wiring
- Dimmable compatible with conventional dimming systems
- Suitable for use in damp locations, wet locations when used with 8563, 8523, and 8568 trims
- Trims include E-26 socket adapter for retro fit use

## Housing

- Sturdy aluminum construction
- Suitable for use in remodel applications
- Adjusts to accommodate various ceiling thickness
- IC Rated for direct contact with batt type fiberglass insulation
- 7-1/2" height allows use in 2" x 8" joist construction

#### **Junction Box**

- J-Box is listed for through-branch circuit wiring (4in - 4out) and eight 1/2" knockouts and four non-metallic cable knockouts with strain relief clamps
- 3-port quick connectors pre-installed in J-box

#### **Dimensions**

- 12-3/4" x 6-1/8" x 7-1/2"
- Aperture: 6-3/8"

## Certifications

- 5 year limited warranty
- cETLus for wet location
- Meets Washington State energy code for restricted air flow requirements









# 8115HRA

120V-277V Universal Voltage

# Specification & Ordering

HOUSING		Example: 8115HRA
Housing	#	
	8115HRA	
	8115HRA	

MODULE/TRIM Example: 8523WH-90-3								
Module/Trim #		Finish	Color Rendering	ССТ	Voltage			
WET	8523							
	<b>8523</b> 5/6" 850lms 12.5W Baffle	WH : White BK : Black OB : Oil Rubbed Bronze BN : Brushed Nickel	-90 : 90CRI	-3K : 3000K -4K : 4000K	-120 : 120V			

MODULE/TRIM Example: 8562WH-80-3								2WH-80-3K	
Module/Trim #		Finish		Color Rendering		CCT		Voltage	
	8562								
	<b>8562</b> 6" 900lms 13W Gimbal	WH BK OB BN	<ul><li>: White</li><li>: Black</li><li>: Oil Rubbed Bronze</li><li>: Brushed Nickel</li></ul>	-80	: 80CRI	-3K	: 3000K	-120	: 120V

MODULE/TRIM Example: 8563WH-90-3H									
Module/Trim #		Finish		Color Rendering		CCT		Voltage	
ν <sub>ε</sub> τ	8563								
	<b>8563</b> 6" 795Ims 13W Reflector	WH BK OB BN CL	<ul><li>: White</li><li>: Black</li><li>: Oil Rubbed Bronze</li><li>: Brushed Nickel</li><li>: Clear</li></ul>	-90	: 90CRI	-3K -4K	3000K 4000K	-120 -277	: 120V : 277V

ORDERING GUIDE Example: 8568WH-90-3K							
Model #		Finish	CRI	CCT			
	8568		-90				
WET	8568 6" LED Baffle Trim with Lens; 17W, 1240 lms	BK: Black OB: Oil Rubbed Bronze CL: Clear WH: White	-90 : 90 CRI	-3K : 3000K* -4K : 4000K			

<sup>\*</sup> Not available in Clear (CL)

TEL: 800.937.6925 | Fax: 800.207.9509 | www.rplighting.com



