

4339-11, 4339-14, 4339-16

120V/277V

Catalog #:		Type
Project:		Date
Prepared by:		

LED Ceiling Mount Fixture



LED Ceiling Mount Fixture

DESCRIPTION

These sleek LED Surface Mount Fixtures are an energy efficient LED light that comes complete with an integrated LED light engine.

DESIGN FEATURES

Construction

- Durable steel construction
- Hard gauge metal back plate and the heat sink to facilitate heat dissipation

Electrical

- 120V/277V
- 120V only: 10-100% Triac dimming
- 50,000 hour projected life
- 90 CRI
- Available in 2700K, 3000K, 3500K, 4000K and 5000K

Lens

- PC diffused lens delivers perfect light distribution

Finish

- Available in white (WH)

Certifications

- cCSAus certified for damp location
- State of California Title 24
- 5 years limited warranty

MOQ

- Minimum Order Quantity: 150



TEL: 800.937.6925 | Fax: 800.207.9509 | www.rplighting.com

Specifications and dimensions subject to change without notice.



RP LIGHTING · FANS

SPECIAL ORDER

4339-11, 4339-14, 4339-16

120V/277V

Specification & Ordering

Model #	Dimensions (L x W x H)	Watts	Lumens	Efficacy (lm/W)
4339-11	11"(0) x 3-1/2"	15W	950lm	63 lm/W
4339-14	14"(0) x 4"	23W	1,300lm	57 lm/W
4339-16	16"(0) x 4-7/16"	34W	2,000lm	59 lm/W

Example: 4339-15-27-90-P-WH

ORDERING	Wattage	CCT	CRI	Diffuser	Finish
4339-11	-15 : 15W	-27K : 2700K	-90 : 90	-P : Plastic	-WH : White
4339-14	-23 : 23W	-3K : 3000K			
4339-16	-24 : 34W	-35K : 3500K			
		-4K : 4000K			
		-5K : 5000K			

LED Ceiling Mount Fixture

SPECIAL ORDER

