

RXL28

120V/277V

Catalog #:		Type
Project:		Date
Prepared by:		

LED Exit Sign, Wet & Cold Location



LED Exit Sign

DESCRIPTION

The RXL28 Series LED Exit Sign, single or double faceplate with snap-in & out chevrons and has a backup battery. Ideal for applications requiring quick-installation exit signs and low energy consumption in wet or cold conditions.

DESIGN FEATURES

Construction

- Polycarbonate lens material and waterproof design suitable for wet and cold location
- Flame retardant thermoplastic enclosure
- Universal snap in and out chevrons that meet new state and local laws UL924 codes
- Manual test switch

Electrical

- 120/277V AC input, 60Hz
- Operating temperature -13°F (-25°C) to 122°F (50°C)
- Contains Ni-cad battery 3.6V 400mAh. Protected from deep discharge. If regular AC fails, the internal solid state transfer switch automatically connects internal battery to run for 90 minutes
- Input power consumption 2.4w Max

Installation

- Easy, one-person installation
- Suitable for wall mount, ceiling mount and end mounting

Dimensions (W x D X H)

- 13" x 2-1/2" x 8-7/8"

Finish

- RW = Red lettering with White Housing
- GW = Green lettering with White Housing

Certifications

- UL924 for wet and cold location listed
- Life Safety NFPA 101
- State of California Title 20 Compliant
- 3 year warranty on components
- 2 year warranty on batteries

ORDERING

Example: RXL28GW

Model #	Finish
RXL28	
RXL28	RW : Red lettering with White Housing GW : Green lettering with White Housing



Batteries Components

TEL: 800.937.6925 | Fax: 800.207.9509 | www.rplighting.com

Specifications and dimensions subject to change without notice.