



22" PRISMATIC SVD SERIES



PRSVD22GV

APPLICATION

22" Lumen Max GV series decorative performance pendant for low, mid-bay and high-bay applications. Prismatic refractor provides horizontal and vertical distribution.

FEATURES

Decorative spun driver housing (SVD) features traditional design. Single-stage optical system for smooth light distribution. 80 CRI minimum. Consult factory for high CRI or special applications. LED module and driver designed for ease of maintenance and replacement. Posi-lock refractor retention ring will absorb shocks and impact. Optional safety cable. Variety of optical lenses and mounting methods.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

ELECTRONICS


GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available, consult factory.

CONSTRUCTION

Housing constructed of extruded and machined aluminum to resist corrosion. Extruded and machined 6063-T5 aluminum heat sink. Refractor made of cast UV stabilized acrylic.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.



A	B	C	D	E
22.4 569.0 mm	13.4 340.4 mm	12.2 309.9 mm	25.6 650.2 mm	13.0 330.2 mm

LUMENS / WATTAGE DATA

PART NUMBER	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
PRSV22GV110L	11000	8807	77	114
PRSV22GV150L	15000	11741	102	115
PRSV22GV180L	18000	14102	116	122

SERIES	LUMENS ¹		CCT	DRIVER / DIMMING ³		OPTIONS ⁴		MOUNTING ⁵		REFRACTOR	DIFFUSER OPTIONS		FINISH ¹⁰				
PRSVD22GV	110L	11000 Lm	27K	2700K	EX	Electronic Driver, 120V/277V	FS	Fusing	HM ⁶	Hang Straight	DF22	22" Diffuse	DOOR DR22A ⁹ 22" Spun Door BC22 22" Band Clamp RS22 ⁹ 22" Refractor Shroud	LENS CN Conical Lens CNFR Conical Lens Frosted DL Drop Lens FO White Optical Acrylic PP Prismatic PC Clear WAG22 22" Wire Guard	MW ¹¹ Matte White MB ¹¹ Matte Black PT ¹¹ Platinum Silver CC Custom Color		
	150L	15000 Lm	30K	3000K												DS10X	10% 0-10V, 120V/277V
	180L	18000 Lm	35K	3500K	DO10X	1% 0-10V, 120V/277V	3CIR	3 Circuit	PM ⁶	Rigid Pendant	OP22	22" Opal					
			40K	4000K												SC1	Driver Safety Cable
			50K	5000K	SC2	Safety Cable, Refractor to Door			HC	Hook & Cord							
																NM2 ^{7/8}	½" NPT Hub
					EMERGENCY BATTERY OPTIONS												
											EMCR	10W Canopy Mounted EM					
											EMRM	7W Remote EM					
											EMEN	7W Remote with Enclosure					
See Page 5 for Full Range of Color Options (83-90081)																	

EXAMPLE: PRSVD22GV150L35KEX/HM36/PR22/DR22ACN/MW

NOTES:

1 Nominal Source Lumens at 35K 2 Nominal Delivered Lumens at 35K at 85 CRI with PR22 3 Contact Factory for Additional Options 4 See Product Options Page for Details 5 See Mounting Page for Details on Components and Finishes 6 Specify Length in Inches: See Mounting Page for Available Lengths 7 Mounting Supplied by Others 8 12" Leads Unless Specified 9 Same Finish as Housing 10 See Color Page for More Options/Consult Factory for Special Finish 11 Standard Finishes



PROJECT: _____

TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.

22" PRISMATIC

SVD SERIES / FIXTURE OPTIONS



STANDARD FINISHES

MW
MATTE WHITE



MB
MATTE BLACK




PT
PLATINUM SILVER




MOUNTING TYPES

HM / AT / PM
HANG STRAIGHT / ALL THREAD / PENDANT




A	B
5.4	2.5
137.2 mm	63.5 mm

CD
CORD / CABLE MOUNT




A	B
5.0	.25
127.0 mm	6.4 mm

HC
HOOK CORD



A
4.2
106.7 mm

NM
NO MOUNT









MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES, CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.
NOTE: THIS IS TYPICAL OF LUMEN MAX SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




MOUNTING TYPES

<p>HM* HANG STRAIGHT 45° SWIVEL 5/8" OD STEM - 3/8" IP</p>  <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p>	<p>PM* RIGID PENDANT MOUNT RIGID 5/8" OD STEM - 3/8" IP</p>  <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLC(XX) Custom Length (Specify in Inches)</p>	<p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 5/8" OD STEM - 1/4" IP</p>  <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT24 - 24" AT36 - 36"</p> 	<p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p>  <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p>	<p>HC HOOK & CORD FOR INDEPENDENT MOUNTING</p>  <p>ORDER: HC</p>
--	---	---	---	---



*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.

EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY





REMOTE EMERGENCY BATTERY OPTIONS



<p>EMRM* - 7W REMOTE EMERGENCY BATTERY (50" MAX)</p>  <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>1.3</td> <td>12.6</td> <td>13.0</td> </tr> </tbody> </table>	A	B	C	1.3	12.6	13.0	<p>EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50" MAX)</p>  <table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>2.0</td> <td>17.0</td> <td>6.2</td> </tr> </tbody> </table>	A	B	C	2.0	17.0	6.2
A	B	C											
1.3	12.6	13.0											
A	B	C											
2.0	17.0	6.2											

*OTHER EM BATTERY SIZES AVAILABLE, CONSULT FACTORY

ADDITIONS

<p>FS - FUSING</p> <p>Slow blow type fuse protects fixture against voltage surges. Factory installed.</p> 	<p>LSP10 - SM - SURGE PROTECTOR</p> <p>Surge protector absorbs transient electrical spikes and protects fixtures and electronics 120/277v. Re-sets after surge. Factory Installed.</p> 
--	---

SAFETY CABLE OPTIONS

<p>SC1 - SAFETY CABLE</p> <p>1/16" stainless steel safety cable for added support. Standard kit is 18" and double barrel locks are provided. Approved for California seismic requirements. Rated at 50 lbs.</p> 	<p>SC2 - SAFETY CABLE</p> <p>1/16" Stainless steel cable holds door to fixture</p> 
--	---

22" PRISMATIC

SVD SERIES / PHOTOMETRIC DATA



PRDDH22LEDGV-180L-35K-Ex/xx/xx/PR22/CNFR/XX

CANDLEPOWER CURVE	INTENSITY	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT									
	0.00°	0° - 10°	589	4%	Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 2		RCR 4			
	0.00° 6,016	0° - 20°	2,500	19%					FC +	W/Sq. Ft.	FC +	W/Sq. Ft.				
	5.00° 5,923	0° - 30°	5,595	42%					22'	20' *	32	0.38	27	0.38		
	10.00° 6,274	0° - 40°	8,621	65%					26'	22' **	20	0.24	17	0.24		
	15.00° 6,868	0° - 60°	11,183	85%					32'	24' ***	18	0.22	10	0.14		
	20.00° 7,058	0° - 80°	11,794	89%					Delivered Illuminance Rating: (DIR)		85 FC per W/Sq. Ft.				70 FC per W/Sq. Ft.	
	30.00° 6,269	0° - 90°	11,971	91%					2' Suspension Length Square rooms used for multiple units: - RCR 2: Length & Width = Ceiling Ht. - 6.5' x 5.00 - RCR 4: Length & Width = Ceiling Ht. - 6.5' x 2.50 + Average Footcandles at 2.5' Above Floor * Exceeds spacing criteria by -4% ** Exceeds spacing criteria by -16% *** Exceeds spacing criteria by -30%							
	40.00° 3,343	Total	13,215	100%												
	50.00° 1,311															
	60.00° 543															
	70.00° 272															
	80.00° 196															
	90.00° 160															
Delivered Lumens: 13,215 Luminaire Watts: 142 LER: 93.06	CP at 0deg (Nadir): 6,016 CRI: 80+	Beam Angle: 78.74 Spacing Ratio: 1.35				Lamp Multiplier: 110L x 0.65, 150L x 0.88, 180L x 1 CCT Multiplier: 50K x 1.07, 40K x 1.03, 30K x 0.983, 27K x 0.967										

COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES

PAINT TIMES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	①
Tier 2 - Typical Finishes	\$\$	①①
Custom Color	Contact Factory	Contact Factory

*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

TIER 1 - STANDARD FINISHES



TIER 2 - TYPICAL FINISHES



CUSTOM COLOR FINISHES

CONTACT FACTORY

CC
Custom Color



*UNAVAILABLE FOR WET LOCATION