



A	B	C	D	E
4.6 117.5 mm	0.6 15.8 mm	3.5 88.9 mm	13.0 330.2 mm	8.0 203.2 mm

3.5" RECESSED WALL WASH

MR16 SERIES / 65 WATT MAX INC

recessed
fixtures



SGLG4X

APPLICATION

3.5" aperture round MR16 lens wall wash.

FEATURES

Wall Wash trim can be rotated, aimed and locked. Integral 5/8" (0.625) plaster ring. Maximum wattage label (**MWL**) for low wattage Halogen or LED lamps. Tool-less transformer access. Multi-bar adjustable mounting brackets.

FINISH

Variety of powdercoat and anodized finishes available on trim. Eco Black (**EB**) finish available on frame/ housing.

ELECTRONICS

120V Electronic transformer is standard.

CONSTRUCTION

Frame constructed of 20 ga. aluminum. Trim spun from .063 high purity aluminum and finished to specification.

LABELS

ETL Listed for Damp Locations. Wet location available. Manufactured and tested to UL Standard No. 1598.

Max Ceiling Thickness:	1.5 (38.1 mm)
Ceiling Cutout:	4.6 Ø (116.8 mm Ø)
Fixture Weight:	4.0 lbs

SERIES	TRANSFORMER	OPTIONS	TRIM / FINISH	TRIM OPTIONS	FIXTURE LAMPING*				
SGLG4X- Spectrum Gold 4" Spread Lensed Wall Wash	E1 -Electronic, 120V E2 -Electronic, 277V MGN1 -Magnetic Transformer 120V MGN2 -Magnetic Transformer 277V E1LED -Transformer for use with LED MR16 lamps 120v NTR - No Transformer	BH27 -27" Bar Hangers (Supplied) BH6 -Expandable Bar Hangers, 6" - 12" BH12 -Expandable Bar Hangers, 12" - 24" CB24 -C-Channel Bars CCEA -Chicago Ceiling Plenum CCEA CR -Corrosion Resistant FS -Fuse Holder and Fuse IC -Insulation Contact (See IC Options) MWL(**) -Maximum Wattage Dedicated Transformer and Label (20w, 37w, 50w) PR -Plaster Ring TBC -T-bar Clips TR -Top Relamping Option EB -Eco Black Housing Finish	AR4200SLWW-SG -Semi-Diffuse Low Iridescent (Standard) CL -Clear Bright Alzak GO -Gold Alzak HZ -Matte Low Iridescent PW -Pewter Alzak UM -Umber Alzak WE -Wheat Alzak BK -Black Finish WH -White Finish PF -Polished Flange	SK -Skytek Linear Lens FG -Frosted (Standard) GS -Gasket SO -Micro Prism Solite™ Lens PG -Prismatic (T73) Lens LN16 -See Recessed Fixtures/ Lens Options for Lens, Louver, and Filter Accessories WL -Wet Location	<table><tr><th>LAMP</th><th>MAX. WATTAGE</th></tr><tr><td>MR-16</td><td>65w</td></tr></table>	LAMP	MAX. WATTAGE	MR-16	65w
	LAMP	MAX. WATTAGE							
MR-16	65w								
		* For Available Louvers and Lenses Consult Factory.	Note: White Flange is Standard.						

EXAMPLE: SGLG4XE1/AR4200SLWW SG GL



PROJECT:

TYPE:



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.