

A B 4.0 11.2 101.6 mm 284.5 mm

Fixture Weight: 7.8 lbs

4" ROUND DIRECT / INDIRECT

FOCUSED ILLUMINATION



C0411UDXT - 2 CABLE MOUNT WITH CORD

APPLICATION

4" round x 11" high mini cylinder luminaire for direct / indirect illumination.

FEATURES

Spectrum's Cylinder series provides traditional architectural style with high performance and energy efficient illumination. Rugged design with flexible mounting, finish and LED options make these extremely versatile fixtures. Interchangeable optics for job site flexibility and fixture upgrade.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes. All exposed materials are chromate pretreated to resist corrosion.

ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 83 with 2-step MacAdam Ellipse binning. High CRI is 98 with 1 x 2-step MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fabricated seamless aluminum fixture housing, specular primary reflector provides high efficiency illumination. Stainless steel hardware with galvanized brackets to resist corrosion. Machined aluminum trims finished to specification.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

LUMENS / WATTAGE DATA								
PART NUMBER	SOURCE LUMENS ¹	SYSTEM WATTS ²						
C0411UDXT7Lx2	1400	12.4						
C0411UDXT10Lx2	2000	18.2						
C0411UDXT13Lx2	2600	26.0						

SERIES		UPLIG	HT			DOWNL	IGHI		С	CT	DRIVE	R / DIMMING4	LENS		MOUNTING ⁶		FINISH	
C0411UDXT	LU	JMENS ¹	OP	TICS	L	UMENS ¹	OP	TICS	83	CRI	EX	Electronic Driver,	GL ⁵	Clear Glass Lens	CD2X7	2 Cable Mount with Cord	MW ⁸	Matte White
	7L	700 Lm	XN ³	12°	7L	700 Lm	XN ³	12°	27K	2700K		120V/277V	so	Micro Prism			MB ⁸	Matte Black
	10L	1000 Lm	ND	21°	10L	1000 Lm	ND	21°	30K	3000K	DS10X	10%, 0-10V,		Solite™ Lens			PT ⁸	Platinum Silver
	13L	1300 Lm	MD	38°	13L	1300 Lm	MD	38°	35K	3500K		120V/277V					CC	Custom Color
			WD	44°			WD	44°	40K	4000K	DO10X	1%, 0-10V,						
												120V/277V						
									98	CRI	DS2W1	ELV/MLV, 120V			EMER	RGENCY BATTERY OPTIONS		ee Page (3)
									27HK	2700K					EMCR	10W Canopy Mounted EM		Full Range of
									30HK	3000K					EMRM	7W Remote EM		olor Options (83-90095)
									35HK	3500K					EMEN	7W Remote with Enclosure		(00-90090)
									40HK	4000K								
									40HK	4000K								

EXAMPLE: C0411UDXT10LMD10LMD35KEX/SO/CD2X72/MW

NOTES:

1 Nominal Source Lumens at Any CCT 2 At 83 CRI 3 XN not Available with 98 CRI Option 4 Contact Factory for Additional Options 5 Standard Lens 6 See Mounting Page for Details on Components and Finishes 7 Specify Length in Inches: See Mounting Page for Available Lengths 8 Standard Finishes 9 See Color Page for More Options/Consult Factory for Special Finishes



PROJECT:
TYPE:







Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may after the performance or appearance of products.

4" ROUND DIRECT / INDIRECT

FOCUSED ILLUMINATION / FIXTURE OPTIONS



STANDARD FINISHES









MOUNTING TYPES

CD2X 2 CABLE MOUNT WITH CORD






EMERGENCY BATTERY OPTIONS



REMOTE EMERGENCY BATTERY OPTIONS



^{*}OTHER EM BATTERY SIZES AVAILABLE, CONSULT FACTORY

COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES

PAINT TIMES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	0
Tier 2 - Typical Finishes	\$\$	00
Custom Color	Contact Factory	Contact Factory

^{*}CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

TIER 1 - STANDARD FINISHES

MW Matte White	GW Gloss White	PT Platinum Silver	MB Matte Black	BZ Bronze

TIER 2 - TYPICAL FINISHES



CUSTOM COLOR FINISHES

CONTACT FACTORY

CC Custom Color



^{*}UNAVAILABLE FOR WET LOCATION

