



WAREHOUSE DOME WITH DOOR

DAMP LOCATION

INTERIOR - CLASSICS

PROJECT: _____
TYPE: _____



WD1812GV
RD - Red Baron



WD1812GV
AZ - Anodic Bronze



WD1812GV
PG - Pub Green



WD1812GV
GA - Galvanized

SERIES	LUMENS ¹		CCT		DRIVER / DIMMING ²		LENS	MOUNTING ³		FINISH ⁷	
WD1611GV WD1812GV	15L	1500 Lm	27K	2700K	EX DS10X DO10X DS2W1	Electronic Driver, 120V/277V 10%, 0-10V, 120V/277V 1%, 0-10V, 120V/277V ELV/MLV, 120V	DR (See 2 nd Page for Ordering Details)	WALL MOUNT		MW ⁸ MB ⁸ PT ⁸ CC	Matte White Matte Black Platinum Silver Custom Color
	27L	2700 Lm	30K	3000K				CP6 PA_4	Wall Mount Cover Mounting Arm Style		
	37L	3700 Lm	35K	3500K				CEILING MOUNT			
	55L	5500 Lm	40K	4000K				HM ⁵ AT ⁵ PM ⁵ CD ⁵ CM ⁵ EMCR ⁶ EMRM EMEN	Hang Straight Hang Straight All Thread Rigid Pendant Mount Cord / Cable Mount Cord Mount 10W Large Driver Canopy EM 7W Remote EM 7W Remote with Enclosure		
See Page 5 for Full Range of Color Options (83-90082)											

EXAMPLE: WD1812GV27L30KEXDR18LD18WA/HM36CH

NOTES:

1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 See Mounting Page for Details on Components and Finishes 4 See Mounting Page for Available Arm Options 5 Specify Length in Inches: See Mounting Page for Available Lengths 6 EMCR Replaces RDC5 or CP13 7 See Color Page for More Options/ Consult Factory for Special Finishes 8 Standard Finishes



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.






WAREHOUSE DOME WITH DOOR DAMP LOCATION INTERIOR - CLASSICS

LUMENS / WATTAGE DATA

PART NUMBER	SOURCE LUMENS ¹	SYSTEM WATTS
WD1611GV15L	1500	10
WD1611GV27L	2700	18
WD1611GV37L	3700	26
WD1611GV55L	5500	39

¹ Nominal Source Lumens at 35K ² Nominal Delivered Lumens at 35K

HOUSING DIMENSIONS



Dimensioned with **WD1812GV**

SERIES	A	B	C
WD1611GV	16.9	14.2	17.2
WD1812GV	18.2	14.8	18.6

APPLICATION

Warehouse Dome is designed for decorative general illumination. Domed decorative lens glows softly. GV Series is designed for damp or dry locations.

FEATURES

Spectrum Lighting's RLM Classics are inspired by vintage lighting fixtures redesigned with modern LED light sources and materials. The wide range of options for illumination, mounting, enclosures, guards and finishes allows for creative fixture specification and design. LED driver is integral to fixture, special driver canopy is required. LED module and driver are serviceable for future replacement. Available in two sizes.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Choice of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall mount canopies are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe and may be field cut. Lens is formed matte white acrylic.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

SERIES SIZES

WD1611GV



WD1812GV



DOORS

DR16C LD16WA - 16" Ø DOOR WITH DOMED MATTE WHITE ACRYLIC

DR18B LD18WA - 18" Ø DOOR WITH DOMED MATTE WHITE ACRYLIC



WD1812GV SHOWN WITH DR18B LD18WA

WALL MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & DIMENSIONS.)

PA

MOUNTING ARM STYLE



CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



CD

CORD / CABLE MOUNT



CM

CORD MOUNT




MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES, CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




WALL MOUNTING

CP104 - SMALL DRIVER CANOPY (STANDARD)
MAY BE USED AS SPLICE BOX FOR DIRECT FEED




CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.




CEILING MOUNTING

HM*
HANG STRAIGHT
45° SWIVEL 1/2" STEM - 3/8" NPT



ORDER: **HM** (Length)
SPECIFY LENGTH:
HM3 - 3" **HM24** - 24"
HM6 - 6" **HM36** - 36"
HM12 - 12" **HM48** - 48"
HM18 - 18" **HM72** - 72"
HMLC(XX)
Custom Length
(Specify in Inches)

AT**
HANG STRAIGHT ALL THREAD
45° SWIVEL 1/2" STEM - 1/4" IP



ORDER: **AT** (Length)
SPECIFY LENGTH:
AT12 - 12"
AT24 - 24"
AT36 - 36"


FIELD CUT THREADED PIPE
1/2" (1/4" MINIMUM)
CUT TYPE COVER SLIP SHORTER
SLIP TYPE COVER OVER THREADED PIPE

PM*
RIGID PENDANT MOUNT
RIGID 1/2" STEM - 3/8" NPT



ORDER: **PM** (Length)
SPECIFY LENGTH:
PM3 - 3" **PM24** - 24"
PM6 - 6" **PM36** - 36"
PM12 - 12" **PM48** - 48"
PM18 - 18" **PM72** - 72"
PMLC(XX)
Custom Length
(Specify in Inches)

CD
CORD / CABLE MOUNT
SJ CORD WITH 1/16 SS CABLE



ORDER: **CD** (Length)
SPECIFY LENGTH:
CD36 - 36"
CD72 - 72"
CD144 - 144"
CDLC(XX)
Custom Length
(Specify in Inches)

CM
CORD MOUNT
SJ CORD WITH STRAIN RELIEF




ORDER: **CM** (Length)
SPECIFY LENGTH:
CM36 - 36"
CM72 - 72"
CM144 - 144"
CMLC(XX)
Custom Length
(Specify in Inches)

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.
**ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT


EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY
(FOR ROUND CEILING MOUNT TYPES)



REMOTE EMERGENCY BATTERY OPTIONS

EMRM* - 7W REMOTE EMERGENCY BATTERY
(50" MAX)



EMEN* - 7W REMOTE EMERGENCY BATTERY
WITH ENCLOSURE (50" MAX)



*OTHER EM BATTERY SIZES AVAILABLE, CONTACT FACTORY.

COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	①
Tier 2 - Typical Finishes	\$\$	①①
Tier 3 - Special Metal Finishes	\$\$\$	①①①
Custom Color	Contact Factory	Contact Factory

*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

TIER 1 - STANDARD FINISHES

MW Matte White	GW Gloss White	PT Platinum Silver	MB Matte Black	GB Gloss Black	BZ Bronze

TIER 2 - TYPICAL FINISHES

TW Textured White	TB Textured Black	MT* Textured Silver	OB* Oil Rubbed Bronze	SN Sun Gold	CO Copper Metallic	BR Brecchia	GH Graphite	CH Charcoal	AL Almond	VE Verde Green
BL Blue Streak	RD Red Baron	OR Orange	CM Carnel	PL Purple	PG Pub Green	TQ Turquoise	SF Sea Foam	PK Pink	AY Aero Yellow	EG Evergreen
LG Lime Green	LB Light Blue	BY Burgundy	AK Anodic Black	AM Anodic Malachite	AZ Anodic Bronze	AS Anodic Sapphire	AN Anodic Natural	AC Anodic Champagne		

TIER 3 - SPECIAL METAL FINISHES

NOT AVAILABLE ON ALL FIXTURES. PLEASE CONSULT SPECIFICATION SHEETS OR FACTORY FOR AVAILABILITY.

GA* Galvanized	BA**/** Brushed Aluminum	GF* Gold Flake

CUSTOM COLOR FINISHES

CONTACT FACTORY

CC
Custom Color



*UNAVAILABLE FOR WET LOCATION

**UNAVAILABLE FOR INTERIOR