



**WAREHOUSE DOME**  
**DAMP LOCATION**  
 INTERIOR - CLASSICS

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_



WD1812GV  
EG - Evergreen



WD1812GV  
OR - Orange



WD1812GV  
GW - Gloss White



WD1812GV  
TQ - Turquoise

SERIES	LUMENS <sup>1</sup>		CCT		DRIVER / DIMMING <sup>2</sup>		ACCESSORIES <sup>3</sup>		MOUNTING <sup>5</sup>		INTERIOR <sup>8</sup>		FINISH <sup>8</sup>	
WD1611GV	15L	1500 Lm	27K	2700K	EX Electronic Driver, 120V/277V DO10X 10%, 0-10V, 120V/277V DS2W1 ELV/MLV, 120V	TF2 <sup>4</sup>	4" Frosted Dome	WALL MOUNT		MWF <sup>9</sup>	Matte White	MW <sup>9</sup>	Matte White	
WD1812GV	27L	2700 Lm	30K	3000K		TG2	4" Dome Wire Guard	CP6	Wall Mount Cover	CCI Custom Color FCI Fixture Color Interior	See Page 5 for Full Range of Color Options (83-90082)	MB <sup>9</sup> Matte Black PT <sup>9</sup> Platinum Silver CC Custom Color		
WD2015GV	37L	3700 Lm	35K	3500K		MF2	4" Frosted Mini	PA <sup>6</sup>	Mounting Arm Style					
	55L	5500 Lm	40K	4000K		MG2	4" Short Wire Guard	CEILING MOUNT						
						FJ2	4" Frosted Tall	HM <sup>7</sup>	Hang Straight					
						FG2	4" Tall Wire Guard	AT <sup>7</sup>	Hang Straight All Thread					
								PM <sup>7</sup>	Rigid Pendant Mount					
								CD <sup>7</sup>	Cord / Cable Mount					
								CM <sup>7</sup>	Cord Mount					
								EMCR	10W Large Driver Canopy EM					
								EMRM	7W Remote EM					
								EMEN	7W Remote with Enclosure					

EXAMPLE: WD1812GV15L30KEXFJ2/HM36MWICH

**NOTES:**

1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 See Enclosures & Guards Page for Wire Guards and Additional Options 4 Standard Enclosure  
 5 See Mounting Page for Details on Components and Finishes 6 See Mounting Page for Available Arm Options 7 Specify Length in Inches: See Mounting Page for Available Lengths  
 8 See Color Page for More Options/Consult Factory for Special Finishes 9 Standard Finishes



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.






# WAREHOUSE DOME DAMP LOCATION INTERIOR - CLASSICS

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
WD1611GV15L	1500	1091	10	109
WD1611GV27L	2700	1906	18	106
WD1611GV37L	3700	2800	26	108
WD1611GV55L	5500	4117	39	106

1 Nominal Source Lumens at 35K 2 Nominal Delivered Lumens at 35K

## HOUSING DIMENSIONS



Dimensioned with **WD1812GV**

SERIES	A	B
WD1611GV	16.5	14.0
WD1812GV	17.9	14.6
WD2015GV	20.0	13.7

## APPLICATION

The Warehouse Dome is designed for decorative general illumination. GV Series is designed for damp or dry locations.

## FEATURES

Spectrum Lighting's RLM Classics are inspired by vintage lighting fixtures redesigned with modern LED light sources and materials. The wide range of options for illumination, mounting, enclosures, guards and finishes allows for creative fixture specification and design. LED driver is integral to fixture, special driver canopy is required. LED module and driver are serviceable for future replacement. Available in three sizes.

## FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available. Interior is Matte White unless specified. Custom Color interior finish available.

## ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Choice of electronic 120V/277V and dimming drivers.

## CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall mount canopies are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe and may be field cut.

## CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

## SERIES SIZES

WD1611GV



WD1812GV



WD2015GV



## WALL MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & DIMENSIONS.)

**PA**  
MOUNTING ARM STYLE



WD1812GV SHOWN WITH PA23

## CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

**HM / AT / PM**  
HANG STRAIGHT / ALL THREAD / PENDANT



WD1812GV SHOWN WITH HM

**CD**  
CORD / CABLE MOUNT



WD1812GV SHOWN WITH CD

**CM**  
CORD MOUNT



WD1812GV SHOWN WITH CM





# WAREHOUSE DOME

## DAMP LOCATION

### INTERIOR - CLASSICS / PHOTOMETRIC DATA

WD1611GV-55L-35K-EX-TF2-MWI

CANDLEPOWER CURVE		INTENSITY		ZONAL LUMENS		SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT																			
		0.00°		0° - 10°	176	4%																							
		0.00°	1,828	0° - 20°	669	16%										6.0'	51 fc	15.1'	19 fc	14'	12'	27	0.28	22	0.28				
		5.00°	1,827	0° - 30°	1,401	34%										8.0'	29 fc	20.2'	11 fc	18'	14'	21	0.21	11	0.14				
		10.00°	1,797	0° - 40°	2,269	55%										10.0'	18 fc	25.2'	7 fc	22'	16'	13	0.13	15	0.18				
		15.00°	1,751	0° - 60°	3,770	92%										12.0'	13 fc	30.3'	5 fc	Delivered Illuminance Rating: (DIR)		99 FC per W/Sq. Ft.		80 FC per W/Sq. Ft.					
		20.00°	1,681	0° - 80°	4,092	99%										14.0'	9 fc	35.3'	3 fc										
		30.00°	1,489	0° - 90°	4,116	100%										16.0'	7 fc	40.4'	3 fc	<div>2' Suspension Length</div> <div>Square rooms used for multiple units:</div> <div>- RCR 2: Length &amp; Width = Ceiling Ht. - 4.5' x 5.00</div> <div>- RCR 4: Length &amp; Width = Ceiling Ht. - 4.5' x 2.50</div> <div>* Average Footcandles at 2.5' Above Floor</div> <div>* Exceeds spacing criteria by 4%</div> <div>** Exceeds spacing criteria by -14%</div> <div>*** Exceeds spacing criteria by -24%</div>									
		40.00°	1,286	Total	4,116	100%										20.0'	5 fc	50.5'	2 fc										
		50.00°	1,005													24.0'	3 fc	60.5'	1 fc										
		60.00°	361																										
		70.00°	138																										
		80.00°	57																										
		90.00°	1																										
Delivered Lumens: 4,116 Luminaire Watts: 39 LER: 105.54		CP at 0deg (Nadir): 1,828 CRI: 85+		Beam Angle: 103.18 Spacing Ratio: 1.21		Lamp Multiplier: 15L x 0.265, 27L x 0.463, 37L x 0.68 CCT Multiplier: 27K x 0.971, 30K x 0.985, 40K x 1.03																							

# MOUNTING & ACCESSORIES


SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES, CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



## ENCLOSURES UP TO 55L



## ENCLOSURE WIRE GUARDS UP TO 55L




## WALL MOUNTING


### CP6/RMD - REMOTE MOUNT DRIVER MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX



CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.




## CEILING MOUNTING




\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS. \*\*ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT

## EMERGENCY BATTERY OPTIONS



## REMOTE EMERGENCY BATTERY OPTIONS



\*OTHER EM BATTERY SIZES AVAILABLE, CONTACT FACTORY.

# COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.  
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



## STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

## PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	①
Tier 2 - Typical Finishes	\$\$	①①
Tier 3 - Special Metal Finishes	\$\$\$	①①①
Custom Color	Contact Factory	Contact Factory

\*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

## TIER 1 - STANDARD FINISHES

<b>MW</b> Matte White	<b>GW</b> Gloss White	<b>PT</b> Platinum Silver	<b>MB</b> Matte Black	<b>GB</b> Gloss Black	<b>BZ</b> Bronze

## TIER 2 - TYPICAL FINISHES

<b>TW</b> Textured White	<b>TB</b> Textured Black	<b>MT*</b> Textured Silver	<b>OB*</b> Oil Rubbed Bronze	<b>SN</b> Sun Gold	<b>CO</b> Copper Metallic	<b>BR</b> Brecchia	<b>GH</b> Graphite	<b>CH</b> Charcoal	<b>AL</b> Almond	<b>VE</b> Verde Green
<b>BL</b> Blue Streak	<b>RD</b> Red Baron	<b>OR</b> Orange	<b>CM</b> Carnel	<b>PL</b> Purple	<b>PG</b> Pub Green	<b>TQ</b> Turquoise	<b>SF</b> Sea Foam	<b>PK</b> Pink	<b>AY</b> Aero Yellow	<b>EG</b> Evergreen
<b>LG</b> Lime Green	<b>LB</b> Light Blue	<b>BY</b> Burgundy	<b>AK</b> Anodic Black	<b>AM</b> Anodic Malachite	<b>AZ</b> Anodic Bronze	<b>AS</b> Anodic Sapphire	<b>AN</b> Anodic Natural	<b>AC</b> Anodic Champagne		

## TIER 3 - SPECIAL METAL FINISHES

NOT AVAILABLE ON ALL FIXTURES. PLEASE CONSULT SPECIFICATION SHEETS OR FACTORY FOR AVAILABILITY.

<b>GA*</b> Galvanized	<b>BA**/**</b> Brushed Aluminum	<b>GF*</b> Gold Flake

## CUSTOM COLOR FINISHES

CONTACT FACTORY

**CC**  
Custom Color



\*UNAVAILABLE FOR WET LOCATION

\*\* UNAVAILABLE FOR INTERIOR