


FEATURES:

- ✓ Architectural luminaire with direct/indirect lighting distribution.
- ✓ Light source: COB LED.
- ✓ Extremely durable round diffuser is made from frosted PMMA Polycarbonate for even lighting distribution.
- ✓ Steel body is available with white or black finish.
- ✓ Suitable for surface and wall mounted installations.
- ✓ LED spot is rated for 60,000hrs. L70 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

ED COR+

SOURCE	RADIANCE	VOLTAGE	DRIVER	MOUNTING	LENS	FINISH	CCT	OPTIONS

Enter the Product Code into the boxes above.

SOURCE

- 15W LED
- 20W LED
- 30W LED

RADIANCE

- DI - Direct Indirect (85%DN/15%Up)
- *Light Distribution.

VOLTAGE

- 120V
 - 277V
 - 347V*
- *Not available for all configurations.

DRIVER

- ST - Standard
 - DL - 0-10V Dimming (1%)
 - DA - DALI
 - *
- * Please specify dimming method (ELV).

MOUNTING

- WM -Wall Mount
- CM-Ceiling Mount

LENS

- OP - Opal

FINISH

- WH - White
- BK - Black
- GR - Grey

CCT

- 30K - 3000Kelvin
 - 35K - 3500Kelvin
 - 40K - 4000Kelvin
 - TW - Tunable White** (2700K-6500K)
- *Other options are available.
**Available with Dali controls.

OPTIONS


- No Options*
 - 90 CRI
- *Leave Empty.

DIMENSIONS:


Height	Width
2.375"	11.5"

LUMEN OUTPUT:

Watts	30K	35K	40K
15W	1360 lm	1400 lm	1440 lm
20W	1850 lm	1900 lm	1950 lm
30W	2800 lm	2900 lm	3000 lm



W



h

Project:

Type: