



FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: LED Strip.
- ✓ Diffused illumination is provided by high efficiency opal insert or optional low glare microprismatic lens.
- ✓ Suitable for non insulated recessed installations in to T-Bar or drywall.
- ✓ Fixture body is made from light weight steel in white finish.
- ✓ LED spot is rated for 60,000hrs. L70 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SOURCE

- 25W LED
- 35W LED

MOUNTING

- RS - Recessed
- DW - Dry Wall

CCT

- 30K - 3000Kelvin
- 35K - 3500Kelvin
- 40K - 4000Kelvin
- TW - Tunable White** (2700K-6500K)

OPTIONS

- No Options*
- 90 CRI
- DS-Daylight Sensor
- OS - Occupancy Sensor
- DOS - Daylight & Occupancy Sensor

VOLTAGE

- 120V
- 277V
- 347V*

* Not available for all configurations.

LENS

- OP - Opal
- PR - Prismatic

*Other options are available.
**Available with Dali controls.

*Leave Empty.
**Combination example (90CRI/DS).



DRIVER

- ST - Standard
- DL - 0-10V Dimming (1%)
- DA - DALI
- EM - Emergency
- *

* Please specify dimming method (ELV).

FINISH

- WH - White
- BK - Black
- GR - Grey



DIMENSIONS:

Length	Width	Height
23.75"	23.75"	1.625"

LUMEN OUTPUT:

Watts	30K	35K	40K
25W	2800 lm	2875 lm	2950 lm
35W	3925 lm	4025 lm	4125 lm

Project:

Type:

SPECIFICATION:

ED CUBE+ SOURCE VOLTAGE DRIVER MOUNTING LENS FINISH CCT OPTIONS

Enter the Product Code into the boxes above.