

FEATURES:

- ✓ Architectural linear luminaire with direct-indirect lighting distribution.
- ✓ Light source: LED Tape.
- ✓ Sleek X-shape design is a unique blend between extruded aluminum body and high efficiency opal lens.
- ✓ Suitable for surface, suspended, wall mounted installations.
- ✓ Offered with integrated built-in LED driver.
- ✓ Aluminum body comes with white, black or grey finish.
- ✓ LED Tape are rated for 60,000hrs. L80 with +85 CRI.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

ED SANT+ SIZE SOURCE RADIANCE VOLTAGE DRIVER MOUNTING LENS FINISH CCT OPTIONS

Enter the Product Code into the boxes above.

SIZE*

- 4Feet
- 6Feet
- 8Feet

*Not suitable for row mounting.

SOURCE

- 5W/Ft LED
- 7W/Ft LED
- 10W/Ft LED

RADIANCE

- DI - Direct Indirect (85%Down-15%Up)

*Light Distribution.

VOLTAGE

- 120V
- 277V
- 347V*

*Not available for all configurations.

DRIVER

- ST - Standard
- DL - 0-10V Dimming (1%)
- DA - DALI
- *
- EC - Emergency Circuit

* Please specify dimming method (ELV).

MOUNTING

- S4-Suspension 4Feet
- S6-Suspension 6Feet
- S Feet*
- WF - Wall Flush
- SF - Surface Mount

*Please specify required Length.

LENS

- OP - Opal

FINISH

- WH - White
- BK - Black
- GR - Grey
- CF - Custom RAL#

CCT


- 30K - 3000Kelvin
- 35K - 3500Kelvin
- 40K - 4000Kelvin
- TW - Tunable White** (2700K-6500K)

*Other options are available.
**Available with Dali controls.

OPTIONS

- No Options*
- 90 CRI
- CB - Casambi BT
- DS-Daylight Sensor
- OS - Occupancy Sensor
- DOS - Daylight & Occupancy Sensor

*Leave Empty.
**Combination example (90CRI/CB).



LUMEN OUTPUT W/Ft:

Watts	30K	35K	40K
5W	515 lm	525 lm	535 lm
7W	720 lm	735 lm	750 lm
10W	1030lm	1050 lm	1080 lm

LENGTH CHART

Size	Length
4 Feet	47.75 Inch
6 Feet	71.75 Inch
8 Feet	95.75 Inch

Project:

Type: