



FEATURES:

- Architectural luminaire with direct lighting distribution.
- Light source: COB LED.
- Available with white aluminum or optional polycarbonate prismatic reflector.
- Suitable for suspended installation.
- Aluminum body with integrated driver. Available in white, black or grey finish.
- LED spot is rated for 60,000hrs. L70 with +85 CRI.
- Has a proven record in office and commercial installations.
- Custom modifications are available.
- ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

ED ZEN+	URCE RADIANCE VOLTAGE DRIVER — Enter ti	MOUNTING REFLECTOR — Product Code into the boxes above.	FINISH CCT	OPTIONS
SOURCE 17W LED 34W LED	RADIANCE DD - Direct (100%Down) *Light Distribution.	VOLTAGE 120V 277V 347V* *Not available for all cont	figurations.	DRIVER ST - Standard DL - 0-10V Dimming DA - DALI * Please specify dimming method (ELV).
MOUNTING S4-Suspension 4F S6-Suspension 6F S Feet* *Please specify required Length.		FINISH WH - White BK - Black GR - Grey	30K - 3000Kelvin 35K - 3500Kelvin 40K - 4000Kelvin *Other options are available.	OPTIONS No Options* 90 CRI *Leave Empty.
DIMENSIONS Heigth Width 13.75" 12.25" LUMEN OUTI				h ! - W -
Watts 30K 17W 1950 lm	35K 40K 2000 lm 2050 lm 4000 lm 4100 lm		Project:	

**** 905-830-0339 / 1-800-667-9281

✓ info@edisonlighting.ca



Type:

www.edisonlighting.ca