

EEXWL Wet Location Incandescent Exit Light



FEATURES

Energy-efficient LED technology in exit sign.
 Easy snap-out chevron directional indicators.
 Combines an EXIT sign & emergency light into one low-profile unit. UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

ELECTRICAL

Dual 120V/277V standard.
 Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
 LVD (low voltage disconnect) prevents battery from deep discharge.
 Long life, maintenance free, rechargeable NiCd battery (EM models).
 Internal solid state transfer switch automatically connects the internal batter to LED board/lamp heads for minimum 90 minute emergency illumination.
 Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

HOUSING

Corrosion-resistant, polycarbonate UV stabilized housing. Removable KO directional indicators.
 Single face only.
 Polycarbonate face plate.

MOUNTING

Knockouts for back mounting.

WARRANTY & LISTING

Five year warranty on all electronics and housing. Battery prorated for five years.

ORDERING INFORMATION

MODEL	LETTER COLOR	BATTERY	OPTIONS
EEXWL			
EEXWL	R - Red G - Green	Blank (AC only) EM - NiCd Battery Backup	HTR - Internal Heater USA - Assembled in the USA



OPTIONS

Using the optional internal heater (HTR) enables the unit to be used in cold environments (contact customer service for more information).

ILLUMINATION

Standard w/ two 5.4W tungsten, adjustable glare-free lighting heads High performance reflector and tempered glass lens for optimal light distribution.
 Ultra bright, energy efficient, long lasting red or green LED (exit sign illumination).
 6" EXIT letters.

DIMENSIONS

