

Contact: _____ Job Name: _____ Ordering Code: _____



AFTER 8 RING PDI

DESCRIPTION

- Super slim 3/16" thick aluminum profile
- Low voltage powered suspension
- 60% direct light output, 40% indirect light output
- Black, brushed nickel or graphite grey finish
- White canopy

ELECTRICAL/CONTROLS

- 54 Watt System
- 120-277V (currently 120V only), 50-60Hz input
- 0-10V dimming to 1% with dim to off

LED INFO

- LED: Luminus MP-3014
- SDCM: 3-step MacAdam Ellipse
- CCT: 2700K/3000K/3500K
- CRI: 90 CRI
- Lumen Maintenance: $L_{70} > 50,000$ hrs
- Delivered Lumens: 2090 lm to 2370 lm

LISTINGS

- ETLus Listed to UL1598 (suitable for indoor use and dry locations only)
- cETL Listed to CSA C22.2 #250.0

ORDERING CODE

Follow the steps to specify your fixture, example: 678 - 00154102341a

Complete Code with X = CCT and YY = Finish

- | | |
|------------------|----------------------------|
| X = CCT | YY = Finish |
| 3 = 2700K | 41 = Black |
| 7 = 3500K | 62 = Brushed nickel |
| 9 = 3000K | 70 = Graphite grey |

AFTER 8 RING PDI

SYS 54W - 60% direct / 40% indirect output

Part Number	Features
678-00154102XYa	2090lm - 2370lm

