## BERETTA SMALL LED

Architectural Indoor

# F



### **FEATURES**

- Acrylic Lens
- ADA Compliant
- Aluminum Construction

PROJECT: TYPE:

COMMENTS:

PO#:

- CRI ≥ 90
- Dimmable @ 120V
- Dimmable to 10%
- ETL Listed For Dry Locations
- LED Light Fixture
- Up or Down Light
- Wall Mounted
- 1 Total Light
- 120V
- ~50,000 Hour Rated LED Life

## LINE DRAWING

3.7"

## FINISHES

Deep Taupe





 TERONLIGHTING.COM

 33 DONALD DR, FAIRFIELD, OH 45014

 P: 513.858.6004

 F: 513.858.6038

 E: SALES@TERONLIGHT.COM

QTY:

LINE DRAWING NOT TO SCALE

# BERETTA SMALL LED

Architectural Indoor

## E 🕕 🖻

PROJECT:	
TYPE:	
PO#:	QTY:
COMMENTS:	

Fixture Core				
PRODUCT CODE	SOURCE/WATTAGE	VOLTAGE	DIMMING DRIVER	
BTS - Beretta Small LED	L3.5-LT350 - 3.5W @ 350mA ELV Low Voltage 2-Wire Dimming Electronic Driver (Leading or Trailing Edge)	120V	ELV or TRIAC Dimming @ 120V	
ORDER INFO				
BTS	L3.5-LT350	120V	ELV, TRIAC	

Example ^

#### Aesthetics & Options

TRIM	FINISH	COLOR TEMP	OPTIONS
Not Applicable	<b>DT</b> - Deep Taupe	<b>30K</b> - 3000K Color Temp	Not Applicable
ORDER INFO	DT	ЗОК	Not Applicable

PROD	SOURCE	30K SPECS		
BTS	L3.5	<ul> <li>30K SPECS</li> <li>30K - 3000K Color Temp</li> <li>310 LED Source Lumens</li> <li>88.6 LED Source Lumens Per Watt</li> <li>185 Delivered LED Lumens</li> <li>52.9 Delivered LED Lumens Per Watt</li> </ul>		

Don't see the configuration you are looking for? Call us today at (513) 858-6004



TERONLIGHTING.COM 33 DONALD DR, FAIRFIELD, OH 45014 P: 513.858.6004 F: 513.858.6038 E: SALES@TERONLIGHT.COM

We reserve the right to revise the design components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice. 2